

On A Theory of Probabilistic Deductive Databases

LAKS V. S. LAKSHMANAN*

*Department of Computer Science
Concordia University
Montreal, Canada*
and

*K.R. School of Information Technology
IIT – Bombay
Mumbai, India*

(e-mail: laks@cs.concordia.ca)

FEREIDOON SADRI†

*Department of Mathematical Sciences
University of North Carolina
Greensboro, NC, USA*
(e-mail: sadri@uncg.edu)

Abstract

We propose a framework for modeling uncertainty where both belief and doubt can be given independent, first-class status. We adopt probability theory as the mathematical formalism for manipulating uncertainty. An agent can express the uncertainty in her knowledge about a piece of information in the form of a *confidence level*, consisting of a pair of intervals of probability, one for each of her belief and doubt. The space of confidence levels naturally leads to the notion of a *trilattice*, similar in spirit to Fitting's bilattices. Intuitively, the points in such a trilattice can be ordered according to truth, information, or precision. We develop a framework for *probabilistic deductive databases* by associating confidence levels with the facts and rules of a classical deductive database. While the trilattice structure offers a variety of choices for defining the semantics of probabilistic deductive databases, our choice of semantics is based on the truth-ordering, which we find to be closest to the classical framework for deductive databases. In addition to proposing a declarative semantics based on valuations and an equivalent semantics based on fixpoint theory, we also propose a proof procedure and prove it sound and complete. We show that while classical Datalog query programs have a polynomial time data complexity, certain query programs in the probabilistic deductive database framework do not even terminate on some input databases. We identify a large natural class of query programs of practical interest in our framework, and show that programs in this class possess polynomial time data complexity, *i.e.* not only do they terminate on every input database, they are guaranteed to do so in a number of steps polynomial in the input database size.

* Research was supported by grants from the Natural Sciences and Engineering Research Council of Canada and NCE/IRIS.

† Research was supported by grants from NSF and UNCG.

1 Introduction

Knowledge-base systems must typically deal with imperfection in knowledge, in particular, in the form of incompleteness, inconsistency, and uncertainty. With this motivation, several frameworks for manipulating data and knowledge have been proposed in the form of extensions to classical logic programming and deductive databases to cope with imperfections in available knowledge. Abiteboul, *et al.* (Abiteboul *et al.*, 1991), Liu (Liu, 1990), and Dong and Lakshmanan (Dong & Lakshmanan, 1992) dealt with deductive databases with incomplete information in the form of null values. Kifer and Lozinskii (Kifer & Lozinskii, 1989; Kifer & Lozinskii, 1992) have developed a logic for reasoning with inconsistency. Extensions to logic programming and deductive databases for handling uncertainty are numerous. They can broadly be categorized into non-probabilistic and probabilistic formalisms. We review previous work in these fields, with special emphasis on probabilistic logic programming, because of its relevance to this paper.

Non-probabilistic Formalisms

(1) *Fuzzy logic programming*: This was essentially introduced by van Emden in his seminal paper on quantitative deduction (van Emden, 1986), and further developed by various researchers, including Steger *et al.* (Steger *et al.*, 1989), Schmidt *et al.* (Schmidt *et al.*, 1989).

(2) *Annotated logic programming*: This framework was introduced by Subrahmanian (Subrahmanian, 1987), and later studied by Blair and Subrahmanian (Blair & Subrahmanian, 1989a; Blair & Subrahmanian, 1989b), and Kifer and Li (Kifer & Li, 1988). While Blair and Subrahmanian's focus was paraconsistency, Kifer and Li extended the framework of (Subrahmanian, 1987) into providing a formal semantics for rule-based systems with uncertainty. Finally, this framework was generalized by Kifer and Subrahmanian into the generalized annotated programming (GAP) framework (Kifer & Subrahmanian, 1992)). All these frameworks are inherently based on a lattice-theoretic semantics. Annotated logic programming has also been employed with the probabilistic approach, which we will discuss further below.

(3) *Evidence theoretic logic programming*: This has been mainly studied by Baldwin and Monk (Baldwin & Monk, 1987) and Baldwin (Baldwin, 1987)). They use Dempster's evidence theory as the basis for dealing with uncertainty in their logic programming framework.

Probabilistic Formalisms

Indeed, there has been substantial amount of research into probabilistic logics ever since Boole (Boole, 1854). Carnap (Carnap, 1962) is a seminal work on probabilistic logic. Fagin, Halpern, and Megiddo (Fagin *et al.*, 1990) study the satisfiability of systems of probabilistic constraints from a model-theoretic perspective. Gaifman (Gaifman, 1964) extends probability theory by borrowing notions and techniques from logic. Nilsson (Nilsson, 1986) uses a "possible worlds" approach to give model-theoretic semantics for probabilistic logic. Hailperin's (Hailperin, 1984) notion of probabilistic entailment is similar to that of Nilsson. Some of the probabilistic logic programming works are based on probabilistic logic approaches, such as Ng and

Subrahmanian’s work on probabilistic logic programming (Ng & Subrahmanian, 1992) and Ng’s recent work on empirical databases (Ng, 1997). We discuss these works further below. We will not elaborate on probabilistic logics any more and refer the reader to Halpern (Halpern, 1990) for additional information.

Works on probabilistic logic programming and deductive databases can be categorized into two main approaches, annotation-based, and implication based.

Annotation Based Approach: Ng and Subrahmanian (Ng & Subrahmanian, 1992) were the first to propose a probabilistic basis for logic programming. Their syntax borrows from that of annotated logic programming (Kifer & Subrahmanian, 1992), although the semantics are quite different. The idea is that uncertainty is always associated with individual atoms (or their conjunctions and disjunctions), while the rules or clauses are always kept classical.

In (Ng & Subrahmanian, 1992), uncertainty in an atom is modeled by associating a probabilistic truth value with it, and by asserting that it lies in an interval. The main interest is in characterizing how precisely we can “bound” the probabilities associated with various atoms. In terms of the terminology of belief and doubt, we can say, following Kifer and Li (Kifer & Li, 1988), that the combination of belief and doubt about a piece of information might lead to an interval of probabilities, as opposed a precise probabilities. But, as pointed out in (Ng & Subrahmanian, 1992), even if one starts with precise point probabilities for atomic events, probabilities associated with compound events can only be calculated to within some exact upper and lower bounds, thus naturally necessitating intervals. But then, the same argument can be made for an agent’s belief as well as doubt about a fact, *i.e.* they both could well be intervals. In this sense, we can say that the model of (Ng & Subrahmanian, 1992) captures only the belief. A second important characteristic of this model is that it makes a conservative assumption that nothing is known about the interdependence of events (captured by the atoms in an input database), and thus has the advantage of not having to make the often unrealistic independence assumption. However, by being conservative, it makes it impossible to take advantage of the (partial) knowledge a user may have about the interdependence among some of the events.

From a technical perspective, only annotation constants are allowed in (Ng & Subrahmanian, 1992). Intuitively, this means only constant probability ranges may be associated with atoms. This was generalized in a subsequent paper by Ng and Subrahmanian (Ng & Subrahmanian, 1993) to allow annotation variables and functions. They have developed fixpoint and model-theoretic semantics, and provided a sound and weakly complete proof procedure. Güntzer *et al.* (Güntzer *et al.*, 1991) have proposed a sound (propositional) probabilistic calculus based on conditional probabilities, for reasoning in the presence of incomplete information. Although they make use of a datalog-based interface to implement this calculus, their framework is actually propositional. In related works, Ng and Subrahmanian have extended their basic probabilistic logic programming framework to capture stable negation in (Ng & Subrahmanian, 1994), and developed a basis for Dempster-Shafer theory in (Ng & Subrahmanian, 1991).

Implication Based Approach: While many of the quantitative deduction frameworks (van Emden (van Emden, 1986), Fitting (Fitting, 1988; Fitting, 1991), Debray and Ramakrishnan (Debray & Ramakrishnan, 1994),¹ etc.) are implication based, the first implication based framework for probabilistic deductive databases was proposed in (Lakshmanan & Sadri, 1994b). The idea behind implication based approach is to associate uncertainty with the facts as well as rules in a deductive database. Sadri (Sadri, 1991b; Sadri, 1991a) in a number of papers developed a hybrid method called Information Source Tracking (IST) for modeling uncertainty in (relational) databases which combines symbolic and numeric approaches to modeling uncertainty. Lakshmanan and Sadri (Lakshmanan & Sadri, 1994a; Lakshmanan & Sadri, 1997) pursue the deductive extension of this model using the implication based approach. Lakshmanan (Lakshmanan, 1994) generalizes the idea behind IST to model uncertainty by characterizing the set of (complex) scenarios under which certain (derived) events might be believed or doubted given a knowledge of the applicable belief and doubt scenarios for basic events. He also establishes a connection between this framework and modal logic. While both (Lakshmanan, 1994; Lakshmanan & Sadri, 1994a) are implication based approaches, strictly speaking, they do not require any commitment to a particular formalism (such a probability theory) for uncertainty manipulation. Any formalism that allows for a consistent calculation of numeric certainties associated with boolean combination of basic events, based on given certainties for basic events, can be used for computing the numeric certainties associated with derived atoms.

Recently, Lakshmanan and Shiri (Lakshmanan & Shiri, 1997) unified and generalized all known implication based frameworks for deductive databases with uncertainty (including those that use formalisms other than probability theory) into a more abstract framework called the parametric framework. The notions of conjunctions, disjunctions, and certainty propagations (via rules) are parameterized and can be chosen based on the applications. Even the domain of certainty measures can be chosen as a parameter. Under such broadly generic conditions, they proposed a declarative semantics and an equivalent fixpoint semantics. They also proposed a sound and complete proof procedure. Finally, they characterized conjunctive query containment in this framework and provided necessary and sufficient conditions for containment for several large classes of query programs. Their results can be applied to individual implication based frameworks as the latter can be seen as instances of the parametric framework. Conjunctive query containment is one of the central problems in query optimization in databases. While the framework of this paper can also be realized as an instance of the parametric framework, the concerns and results there are substantially different from ours. In particular, to our knowledge, this is the first paper to address data complexity in the presence of (probabilistic) uncertainty.

¹ The framework proposed in (Debray & Ramakrishnan, 1994) unifies Horn clause based computations in a variety of settings, including that of quantitative deduction as proposed by van Emden (van Emden, 1986), within one abstract formalism. However, in view of the assumptions made in (Debray & Ramakrishnan, 1994), not all probabilistic conjunctions and disjunctions are permitted by that formalism.

Other Related Work

Fitting (Fitting, 1988; Fitting, 1991) has developed an elegant framework for quantitative logic programming based on bilattices, an algebraic structure proposed by Ginsburg (Ginsburg, 1988) in the context of many-valued logic programming. This was the first to capture both belief and doubt in one uniform logic programming framework. In recent work, Lakshmanan *et al.* (Lakshmanan *et al.*, 1997) have proposed a model and algebra for probabilistic relational databases. This framework allows the user to choose notions of conjunctions and disjunctions based on a family of strategies. In addition to developing complexity results, they also address the problem of efficient maintenance of materialized views based on their probabilistic relational algebra. One of the strengths of their model is not requiring any restrictive independence assumptions among the facts in a database, unlike previous work on probabilistic relational databases (Barbara *et al.*, 1992). In a more recent work, Dekhtyar and Subrahmanian (Dekhtyar & Subrahmanian, 1997) developed an annotation based framework where the user can have a parameterized notion of conjunction and disjunction. In not requiring independence assumptions, and being able to allow the user to express her knowledge about event interdependence by means of a parametrized family of conjunctions and disjunctions, both (Dekhtyar & Subrahmanian, 1997; Lakshmanan *et al.*, 1997) have some similarities to this paper. However, chronologically, the preliminary version of this paper (Lakshmanan & Sadri, 1994b) was the first to incorporate such an idea in a probabilistic framework. Besides, the frameworks of (Dekhtyar & Subrahmanian, 1997; Lakshmanan *et al.*, 1997) are substantially different from ours. In a recent work Ng (Ng, 1997) studies *empirical* databases, where a deductive database is enhanced by empirical clauses representing statistical information. He develops a model-theoretic semantics, and studies the issues of consistency and query processing in such databases. His treatment is probabilistic, where probabilities are obtained from statistical data, rather than being subjective probabilities. (See Halpern (Halpern, 1990) for a comprehensive discussion on statistical and subjective probabilities in logics of probability.) Ng's query processing algorithm attempts to resolve a query using the (regular) deductive component of the database. If it is not successful, then it reverts to the empirical component, using the notion of *most specific reference class* usually used in statistical inferences. Our framework is quite different in that every rule/fact is associated with a confidence level (a pair of probabilistic intervals representing belief and doubt), which may be subjective, or may have been obtained from underlying statistical data. The emphasis of our work is on (i) the characterization of different modes for combining confidences, (ii) semantics, and, in particular, (iii) termination and complexity issues.

The contributions of this paper are as follows.

- We associate a *confidence level* with facts and rules (of a deductive database). A confidence level comes with both a *belief* and a *doubt*² (in what is being

² We specifically avoid the term *disbelief* because of its possible implication that it is the comple-

asserted) [see Section 2 for a motivation]. Belief and doubt are subintervals of $[0, 1]$ representing probability ranges.

- We show that confidence levels have an interesting algebraic structure called *trilattices* as their basis (Section 3). Analogously to Fitting’s bilattices, we show that trilattices associated with confidence levels are interlaced, making them interesting in their own right, from an algebraic point of view. In addition to providing an algebraic footing for our framework, trilattices also shed light on the relationship between our work and earlier works and offer useful insights. In particular, trilattices give rise to three ways of ordering confidence levels: the truth-order, where belief goes up and doubt comes down, the information order, where both belief and doubt go up, and the precision order, where the probability intervals associated with both belief and doubt become sharper, *i.e.* the interval length decreases. This is to be contrasted with the known truth and information (called knowledge there) orders in a bilattice.
- A purely lattice-theoretic basis for logic programming can be constructed using trilattices (similar to Fitting (Fitting, 1991)). However, since our focus in this paper is probabilistic uncertainty, we develop a probabilistic calculus for combining confidence levels associated with basic events into those for compound events based on them (Section 4). Instead of committing to any specific rules for combining confidences, we propose a framework which allows a user to choose an appropriate “mode” from a collection of available ones.
- We develop a generalized framework for rule-based programming with probabilistic knowledge, based on this calculus. We provide the declarative and fixpoint semantics for such programs and establish their equivalence (Section 5). We also provide a sound and complete proof procedure (Section 6).
- We study the termination and complexity issues of such programs and show: (1) the closure ordinal of T_P can be as high as ω in general (but no more), and (2) when only *positive correlation* is used for disjunction³, the data complexity of such programs is polynomial time. Our proof technique for the last result yields a similar result for van Emden’s framework (Section 7).
- We also compare our work with related work and bring out the advantages and generality of our approach (Section 7).

2 Motivation

In this section, we discuss the motivation for our work as well as comment on our design decisions for this framework. The motivation for using probability theory as opposed to other formalisms for representing uncertainty has been discussed at length in the literature (Carnap, 1962; Ng & Subrahmanian, 1992). Probability theory is perhaps the best understood and mathematically well-founded paradigm in which uncertainty can be modeled and reasoned about. Two possibilities for

ment of belief, in some sense. In our framework, doubt is not necessarily the truth-functional complement of belief.

³ Other modes can be used (for conjunction/disjunction) in the “non-recursive part” of the program.

associating probabilities with facts and rules in a DDB are van Emden's style of associating confidences with rules as a whole (van Emden, 1986), or the annotation style of Kifer and Subrahmanian (Kifer & Subrahmanian, 1992). The second approach is more powerful: It is shown in (Kifer & Subrahmanian, 1992) that the second approach can simulate the first. The first approach, on the other hand, has the advantage of intuitive appeal, as pointed out by Kifer and Subrahmanian (Kifer & Subrahmanian, 1992). In this paper, we choose the first approach. A comparison between our approach and annotation-based approach with respect to termination and complexity issues is given in Section 7.

A second issue is whether we should insist on precise probabilities or allow intervals (or ranges). Firstly, probabilities derived from any sources may have tolerances associated with them. Even experts may feel more comfortable with specifying a range rather than a precise probability. Secondly, Fenstad (Fenstad, 1980) has shown (also see (Ng & Subrahmanian, 1992)) that when enough information is not available about the interaction between events, the probability of compound events cannot be determined precisely: one can only give (tight) bounds. Thus, we associate ranges of probabilities with facts and rules.

A last issue is the following. Suppose (uncertain) knowledge contributed by an expert corresponds to the formula F . In general, we cannot assume the expert's knowledge is perfect. This means he does not necessarily know *all* situations in which F holds. Nor does he know *all* situations where F fails to hold (*i.e.* $\neg F$ holds). He models the proportion of the situations where he knows F holds as his *belief* in F and the proportion of situations where he knows $\neg F$ holds as his *doubt*. There could be situations, unknown to our expert, where F holds (or $\neg F$ holds). These unknown situations correspond to the gap in his knowledge. Thus, as far as he knows, F is *unknown* or *undefined* in these remaining situations. These observations, originally made by Fitting (Fitting, 1988), give rise to the following definition.

Definition 2.1

(*Confidence Level*) Denote by $\mathcal{C}[0, 1]$ the set of all closed subintervals over $[0, 1]$. Consider the set $\mathcal{L}_c =_{def} \mathcal{C}[0, 1] \times \mathcal{C}[0, 1]$. A *Confidence Level* is an element of $\mathcal{L}_c$. We denote a confidence level as $\langle [\alpha, \beta], [\gamma, \delta] \rangle$.

In our approach confidence levels are associated with facts and rules. The intended meaning of a fact (or rule) F having a confidence $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ is that α and β are the lower and upper bounds of the expert's *belief* in F , and γ and δ are the lower and upper bounds of the expert's *doubt* in F . These notions will be formalized in Section 4.

The following example illustrates such a scenario. (The figures in all our examples are fictitious.)

Example 2.1

Consider the results of Gallup polls conducted before the recent Canadian federal elections.

1. Of the people surveyed, between 50% and 53% of the people in the age group 19

to 30 favor the liberals.

2. Between 30% and 33% of the people in the above age group favor the reformists.
3. Between 5% and 8% of the above age group favor the tories.

The reason we have ranges for each category is that usually some tolerance is associated with the results coming from such polls. Also, we do not make the proportion of undecided people explicit as our interest is in determining the support for the different parties. Suppose we assimilate the information above in a probabilistic framework. For each party, we compute the probability that a *randomly* chosen person from the sample population of the given age group will (not) vote for that party. We transfer this probability as the *subjective* probability that *any* person from that age group (in the actual population) will (not) vote for the party. The conclusions are given below, where $vote(X, P)$ says X will vote for party P , $age\text{-}group1(X)$ says X belongs to the age group specified above. *liberals*, *reform*, and *tories* are constants, with the obvious meaning.

1. $vote(X, liberals) \xleftarrow{\langle [0.5, 0.53], [0.35, 0.41] \rangle} age\text{-}group1(X).$
2. $vote(X, reform) \xleftarrow{\langle [0.3, 0.33], [0.55, 0.61] \rangle} age\text{-}group1(X).$
3. $vote(X, tories) \xleftarrow{\langle [0.05, 0.08], [0.8, 0.86] \rangle} age\text{-}group1(X).$

As usual, each rule is implicitly universally quantified outside the entire rule. Each rule is expressed in the form

$$A \xleftarrow{\langle [\alpha, \beta], [\gamma, \delta] \rangle} Body$$

where $\alpha, \beta, \gamma, \delta \in [0, 1]$. We usually require that $\alpha \leq \beta$ and $\gamma \leq \delta$. With each rule, we have associated two intervals. $[\alpha, \beta]$ ($[\gamma, \delta]$) is the *belief* (*doubt*) the expert has in the rule. Notice that from his knowledge, the expert can only conclude that the proportion of people he *knows* favor *reform* or *tories* will not vote for *liberals*. Thus the probability that a person in the age group 19-30 will not vote for liberals, according to the expert's knowledge, is in the range $[0.35, 0.41]$, obtained by summing the endpoints of the belief ranges for reform and tories. Notice that in this case $\alpha + \delta$ (or $\beta + \gamma$) is not necessarily 1. This shows we cannot regard the expert's doubt as the complement (with respect to 1) of his belief. Thus, if we have to model what *necessarily* follows according to the expert's knowledge, then we must carry both the belief and the doubt explicitly. Note that this example suggests just one possible means by which confidence levels could be obtained from statistical data. As discussed before, gaps in an expert's knowledge could often directly result in both belief and doubt. In general, there could be many ways in which both belief and doubt could be obtained and associated with the basic facts. Given this, we believe that an independent treatment of both belief and doubt is both necessary and interesting for the purpose of obtaining the confidence levels associated with derived facts. Our approach to independently capture belief and doubt makes it possible to cope with incomplete knowledge regarding the situations in which an event is true, false, or unknown in a general setting.

Kifer and Li (Kifer & Li, 1988) and Baldwin (Baldwin, 1987) have argued that incorporating both belief and doubt (called disbelief there) is useful in dealing

with incomplete knowledge, where different evidences may contradict each other. However, in their frameworks, doubt need not be maintained explicitly. For suppose we have a belief b and a disbelief d associated with a phenomenon. Then they can both be absorbed into one range $[b, 1 - d]$ indicating that the effective certainty ranges over this set. The difference with our framework, however, is that we model what is *known* definitely, as opposed to what is *possible*. This makes (in our case) an explicit treatment of belief and doubt mandatory.

3 The Algebra of Confidence Levels

Fitting (Fitting, 1991) has shown that *bilattices* (introduced by Ginsburg (Ginsburg, 1988)) lead to an elegant framework for quantified logic programming involving both belief and doubt. In this section, we shall see that a notion of *trilattices* naturally arises with confidence levels. We shall establish the structure and properties of trilattices here, which will be used in later sections.

Definition 3.1

Denote by $\mathcal{C}[0, 1]$ the set of all closed subintervals over $[0, 1]$. Consider the set $\mathcal{L}_c =_{\text{def}} \mathcal{C}[0, 1] \times \mathcal{C}[0, 1]$. We denote the elements of $\mathcal{L}_c$ as $\langle [\alpha, \beta], [\gamma, \delta] \rangle$. Define the following orders on this set. Let $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle, \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$ be any two elements of $\mathcal{L}_c$.

$\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \leq_t \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$ iff $\alpha_1 \leq \alpha_2, \beta_1 \leq \beta_2$ and $\gamma_2 \leq \gamma_1, \delta_2 \leq \delta_1$
 $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \leq_k \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$ iff $\alpha_1 \leq \alpha_2, \beta_1 \leq \beta_2$ and $\gamma_1 \leq \gamma_2, \delta_1 \leq \delta_2$
 $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \leq_p \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$ iff $\alpha_1 \leq \alpha_2, \beta_2 \leq \beta_1$ and $\gamma_1 \leq \gamma_2, \delta_2 \leq \delta_1$

Some explanation is in order. The order $\leq_t$ can be considered the *truth* ordering: “truth” relative to the expert’s knowledge increases as belief goes up and doubt comes down. The order $\leq_k$ is the *knowledge* (or information) ordering: “knowledge” (*i.e.* the extent to which the expert commits his opinion on an assertion) increases as both belief and doubt increase. The order $\leq_p$ is the *precision* ordering: “precision” of information supplied increases as the probability intervals become narrower. The first two orders are analogues of similar orders in bilattices. The third one, however, has no counterpart there. It is straightforward to see that each of the orders $\leq_t$, $\leq_k$, and $\leq_p$ is a partial order. $\mathcal{L}_c$ has a least and a greatest element with respect to each of these orders. In the following, we give the definition of meet and join with respect to the $\leq_t$ order. Operators with respect to the other orders have a similar definition.

Definition 3.2

Let $\langle \mathcal{L}_c, \leq_t, \leq_k, \leq_p \rangle$ be as defined in Definition 3.1. Then the meet and join corresponding to the truth, knowledge (information), and precision orders are defined as follows. The symbols $\otimes$ and $\oplus$ denote meet and join, and the subscripts t, k , and p represent truth, knowledge, and precision, respectively.

1. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \otimes_t \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\min\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle.$

2. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \oplus_t \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\max\{\alpha_1, \alpha_2\}, \max\{\beta_1, \beta_2\}], [\min\{\gamma_1, \gamma_2\}, \min\{\delta_1, \delta_2\}] \rangle.$
3. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \otimes_k \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\min\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\min\{\gamma_1, \gamma_2\}, \min\{\delta_1, \delta_2\}] \rangle.$
4. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \oplus_k \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\max\{\alpha_1, \alpha_2\}, \max\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle.$
5. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \otimes_p \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\min\{\alpha_1, \alpha_2\}, \max\{\beta_1, \beta_2\}], [\min\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle.$
6. $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \oplus_p \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle =$
 $\langle [\max\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \min\{\delta_1, \delta_2\}] \rangle.$

The top and bottom elements with respect to the various orders are as follows. The subscripts indicate the associated orders, as usual.

$$\begin{aligned} \top_t &= \langle [1, 1], [0, 0] \rangle, & \perp_t &= \langle [0, 0], [1, 1] \rangle, \\ \top_k &= \langle [1, 1], [1, 1] \rangle, & \perp_k &= \langle [0, 0], [0, 0] \rangle, \\ \top_p &= \langle [1, 0], [1, 0] \rangle, & \perp_p &= \langle [0, 1], [0, 1] \rangle. \end{aligned}$$

$\top_t$ corresponds to total belief and no doubt; $\perp_t$ is the opposite. $\top_k$ represents maximal information (total belief and doubt), to the point of being probabilistically inconsistent: belief and doubt probabilities sum to more than 1; $\perp_k$ gives the least information: no basis for belief or doubt; $\top_p$ is maximally precise, to the point of making the intervals empty (and hence inconsistent, in a non-probabilistic sense); $\perp_p$ is the least precise, as it imposes only trivial bounds on belief and doubt probabilities.

Fitting (Fitting, 1991) defines a bilattice to be *interlaced* whenever the meet and join with respect to any order of the bilattice are monotone with respect to the other order. He shows that it is the interlaced property of bilattices that makes them most useful and attractive. We say that a trilattice is *interlaced* provided the meet and join with respect to any order are monotone with respect to any other order. We have

Lemma 3.1

The trilattice $\langle \mathcal{L}_c, \leq_t, \leq_k, \leq_p \rangle$ defined above is interlaced.

Proof. Follows directly from the fact that *max* and *min* are monotone functions. We show the proof for just one case. Let $\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \leq_p \langle [\alpha_3, \beta_3], [\gamma_3, \delta_3] \rangle$ and $\langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle \leq_p \langle [\alpha_4, \beta_4], [\gamma_4, \delta_4] \rangle$. Then

$$\begin{aligned} \langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \otimes_t \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle &= \\ \langle [\min\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle & \\ \langle [\alpha_3, \beta_3], [\gamma_3, \delta_3] \rangle \otimes_t \langle [\alpha_4, \beta_4], [\gamma_4, \delta_4] \rangle &= \\ \langle [\min\{\alpha_3, \alpha_4\}, \min\{\beta_3, \beta_4\}], [\max\{\gamma_3, \gamma_4\}, \max\{\delta_3, \delta_4\}] \rangle & \end{aligned}$$

Since $\alpha_1 \leq \alpha_3, \beta_1 \leq \beta_3, \alpha_2 \leq \alpha_4, \beta_2 \leq \beta_4$, we have $\min\{\alpha_1, \alpha_2\} \leq \min\{\alpha_3, \alpha_4\}$, and $\min\{\beta_1, \beta_2\} \leq \min\{\beta_3, \beta_4\}$. Similarly, $\max\{\gamma_1, \gamma_2\} \leq \max\{\gamma_3, \gamma_4\}$ and $\max\{\delta_1, \delta_2\} \leq \max\{\delta_3, \delta_4\}$. This implies

$$\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \otimes_t \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle \leq_p \langle [\alpha_3, \beta_3], [\gamma_3, \delta_3] \rangle \otimes_t \langle [\alpha_4, \beta_4], [\gamma_4, \delta_4] \rangle$$

Other cases are similar. ■

Trilattices are of independent interest in their own right, from an algebraic point of view. We also stress that they can be used as a basis for developing quantified/annotated logic programming schemes (which need not be probabilistic). This will be pursued in a future paper.

In closing this section, we note that other orders are also possible for confidence levels. In fact, Fitting has shown that a fourth order, denoted by $\leq_f$ in the following, together with the three orders defined above, forms an interlaced “quadri-lattice” (Fitting, 1995). He also pointed out that this “quadri-lattice” can be generated as the cross product of two bilattices. Intuitively, a confidence level increases according to this fourth ordering, when the precision of the belief component of a confidence level goes up, while that of the doubt component goes down. That is,

$$\langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle \leq_f \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle \text{ iff } \alpha_1 \leq \alpha_2, \beta_2 \leq \beta_1 \text{ and } \gamma_2 \leq \gamma_1, \delta_1 \leq \delta_2$$

In our opinion, the fourth order, while technically elegant, does not have the same intuitive appeal as the three orders – truth, knowledge, and precision – mentioned above. Hence, we do not consider it further in this paper. The algebraic properties of confidence levels and their underlying lattices are interesting in their own right, and might be used for developing alternative bases for quantitative logic programming. This issue is orthogonal to the concerns of this paper.

4 A Probabilistic Calculus

Given the confidence levels for (basic) events, how are we to derive the confidence levels for compound events which are based on them? Since we are working with probabilities, our combination rules must respect probability theory. We need a model of our knowledge about the interaction between events. A simplistic model studied in the literature (*e.g.* see Barbara *et al.* (Barbara *et al.*, 1990)) assumes *independence* between all pairs of events. This is highly restrictive and is of limited applicability. A general model, studied by Ng and Subrahmanian (Ng & Subrahmanian, 1992; Ng & Subrahmanian, 1993) is that of *ignorance*: assume no knowledge about event interaction. Although this is the most general possible situation, it can be overly conservative when *some* knowledge is available, concerning some of the events. We argue that for “real-life” applications, no single model of event interaction would suffice. Indeed, we need the ability to “parameterize” the model used for event interaction, depending on what *is* known about the events themselves. In this section, we develop a probabilistic calculus which allows the user to select an appropriate “mode” of event interaction, out of several choices, to suit his needs.

Let $\mathbf{L}$ be an arbitrary, but fixed, first-order language with finitely many constants, predicate symbols, infinitely many variables, and no function symbols⁴. We use (ground) atoms of $\mathbf{L}$ to represent basic events. We blur the distinction between an event and the formula representing it. Our objective is to characterize confidence

⁴ In deductive databases, it is standard to restrict attention to function free languages. Since input databases are finite (as they are in reality), this leads to a finite Herbrand base.

levels of boolean combinations of events involving the connectives $\neg, \wedge, \vee$, in terms of the confidence levels of the underlying basic events under various modes (see below).

We gave an informal discussion of the meaning of confidence levels in Section 2. We use the concept of *possible worlds* to formalize the semantics of confidence levels.

Definition 4.1

(*Semantics of Confidence Levels*) According to the expert's knowledge, an event F can be true, false, or unknown. This gives rise to 3 possible worlds. Let $1, 0, \perp$ respectively denote *true*, *false*, and *unknown*. Let W_i denote the world where the truth-value of F is i , $i \in \{0, 1, \perp\}$, and let w_i denote the probability of the world W_i . Then the assertion that the confidence level of F is $\langle [\alpha, \beta], [\gamma, \delta] \rangle$, written $\text{conf}(F) = \langle [\alpha, \beta], [\gamma, \delta] \rangle$, corresponds to the following constraints:

$$\begin{aligned} \alpha &\leq w_1 \leq \beta \\ \gamma &\leq w_0 \leq \delta \\ w_i &\geq 0, \quad i \in \{1, 0, \perp\} \\ \sum_i w_i &= 1 \end{aligned} \tag{1}$$

where α and β are the lower and upper bounds of the *belief* in F , and γ and δ are the lower and upper bounds of the *doubt* in F .

Equation (1) imposes certain restrictions on confidence levels.

Definition 4.2

(*Consistent confidence levels*) We say a confidence level $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ is *consistent* if Equation (1) has an answer.

It is easily seen that:

Proposition 4.1

Confidence level $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ is *consistent* provided (i) $\alpha \leq \beta$ and $\gamma \leq \delta$, and (ii) $\alpha + \gamma \leq 1$.

The consistency condition guarantees at least one solution to Equation (1). However, given a confidence level $\langle [\alpha, \beta], [\gamma, \delta] \rangle$, there may be w_1 values in the $[\alpha, \beta]$ interval for which no w_0 value exists in the $[\gamma, \delta]$ interval to form an answer to Equation (1), and vice versa. We can “trim” the upperbounds of $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ as follows to guarantee that for each value in the $[\alpha, \beta]$ interval there is at least one value in the $[\gamma, \delta]$ interval which form an answer to Equation (1).

Definition 4.3

(*Reduced confidence level*) We say a confidence level $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ is *reduced* if for all $w_1 \in [\alpha, \beta]$ there exist $w_0, w_\perp$ such that $w_1, w_0, w_\perp$ is a solution to Equation (1), and for all $w_0 \in [\gamma, \delta]$ there exist $w_1, w_\perp$ such that $w_1, w_0, w_\perp$ is a solution to Equation (1).

It is obvious that a reduced confidence level is consistent.

Proposition 4.2

Confidence level $\langle [\alpha, \beta], [\gamma, \delta] \rangle$ is *reduced* provided (i) $\alpha \leq \beta$ and $\gamma \leq \delta$, and (ii) $\alpha + \delta \leq 1$, and $\beta + \gamma \leq 1$.

Proposition 4.3

Let $c = \langle [\alpha, \beta], [\gamma, \delta] \rangle$ be a consistent confidence level. Let $\beta' = 1 - \gamma$ and $\delta' = 1 - \alpha$. Then, the confidence level $c' = [\alpha, \min(\beta, \beta')], [\gamma, \min(\delta, \delta')]$ is a reduced confidence level. Further, c and c' are probabilistically equivalent, in the sense that they produce exactly the same answer sets to Equation (1).

Data in a probabilistic deductive database, that is, facts and rules that comprise the database, are associated with confidence levels. At the atomic level, we require the confidence levels to be consistent. This means each expert, or data source, should be consistent with respect to the confidence levels it provides. This does not place any restriction on data provided by different experts/sources, as long as each is individually consistent. Data provided by different experts/sources should be combined, using an appropriate combination mode (discussed in next section). We will show that the combination formulas for the various modes preserve consistent as well as reduced confidence levels.

4.1 Combination Modes

Now, we introduce the various modes and characterize conjunction and disjunction under these modes. Let F and G represent two arbitrary ground (*i.e.* variable-free) formulas. For a formula F , $\text{conf}(F)$ will denote its confidence level. In the following, we describe several interesting and natural modes and establish some results on the confidence levels of conjunction and disjunction under these modes. Some of the modes are well known, although care needs to be taken to allow for the 3-valued nature of our framework.

1. *Ignorance*: This is the most general situation possible: nothing is assumed/known about event interaction between F and G . The extent of the interaction between F and G could range from maximum overlap to minimum overlap.
2. *Independence*: This is a well-known mode. It simply says (non-)occurrence of one event does not influence that of the other.
3. *Positive Correlation*: This mode corresponds to the knowledge that the occurrences of two events overlap as much as possible. This means the conditional probability of one of the events (the one with the larger probability) given the other is 1.
4. *Negative Correlation*: This is the exact opposite of positive correlation: the occurrences of the events overlap minimally.
5. *Mutual Exclusion*: This is a special case of negative correlation, where we know that the sum of probabilities of the events does not exceed 1.

We have the following results.

Proposition 4.4

Let F be any event, and let $\text{conf}(F) = \langle [\alpha, \beta], [\gamma, \delta] \rangle$. Then $\text{conf}(\neg F) = \langle [\gamma, \delta], [\alpha, \beta] \rangle$. Thus, negation simply swaps belief and doubt.

Proof. Follows from the observation that $\text{conf}(F) = \langle [\alpha, \beta], [\gamma, \delta] \rangle$ implies that $\alpha \leq w_1 \leq \beta$ and $\gamma \leq w_0 \leq \delta$, where w_1 (w_0) denotes the probability of the possible world where event F is true (false). ■

The following theorem establishes the confidence levels of compound formulas as a function of those of the constituent formulas, under various modes.

Theorem 4.1

Let F and G be any events and let $\text{conf}(F) = \langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle$ and $\text{conf}(G) = \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$. Then the confidence levels of the compound events $F \wedge G$ and $F \vee G$ are given as follows. (In each case the subscript denotes the mode.)

$$\begin{aligned}
\text{conf}(F \wedge_{ig} G) &= \langle [\max\{0, \alpha_1 + \alpha_2 - 1\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle. \\
\text{conf}(F \vee_{ig} G) &= \langle [\max\{\alpha_1, \alpha_2\}, \min\{1, \beta_1 + \beta_2\}], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \min\{\delta_1, \delta_2\}] \rangle. \\
\text{conf}(F \wedge_{ind} G) &= \langle [\alpha_1 \times \alpha_2, \beta_1 \times \beta_2], [1 - (1 - \gamma_1) \times (1 - \gamma_2), 1 - (1 - \delta_1) \times (1 - \delta_2)] \rangle. \\
\text{conf}(F \vee_{ind} G) &= \langle [1 - (1 - \alpha_1) \times (1 - \alpha_2), 1 - (1 - \beta_1) \times (1 - \beta_2)], [\gamma_1 \times \gamma_2, \delta_1 \times \delta_2] \rangle. \\
\text{conf}(F \wedge_{pc} G) &= \langle [\min\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle. \\
\text{conf}(F \vee_{pc} G) &= \langle [\max\{\alpha_1, \alpha_2\}, \max\{\beta_1, \beta_2\}], [\min\{\gamma_1, \gamma_2\}, \min\{\delta_1, \delta_2\}] \rangle. \\
\text{conf}(F \wedge_{nc} G) &= \langle [\max\{0, \alpha_1 + \alpha_2 - 1\}, \max\{0, \beta_1 + \beta_2 - 1\}], [\min\{1, \gamma_1 + \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle. \\
\text{conf}(F \vee_{nc} G) &= \langle [\min\{1, \alpha_1 + \alpha_2\}, \min\{1, \beta_1 + \beta_2\}], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \max\{0, \delta_1 + \delta_2 - 1\}] \rangle. \\
\text{conf}(F \wedge_{me} G) &= \langle [0, 0], [\min\{1, \gamma_1 + \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle. \\
\text{conf}(F \vee_{me} G) &= \langle [\alpha_1 + \alpha_2, \beta_1 + \beta_2], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \max\{0, \delta_1 + \delta_2 - 1\}] \rangle.
\end{aligned}$$

Proof. Each mode is characterized by a system of constraints, and the confidence level of the formulas $F \wedge G, F \vee G$ are obtained by extremizing certain objective functions subject to these constraints.

The scope of the possible interaction between F and G can be characterized as follows (also see (Frechet, M., 1935; Ng & Subrahmanian, 1992)). According to the expert's knowledge, each of F, G can be true, false, or unknown. This gives rise to 9 possible worlds. Let 1, 0, $\perp$ respectively denote *true*, *false*, and *unknown*. Let W_{ij} denote the world where the truth-value of F is i and that of G is j , $i, j \in \{1, 0, \perp\}$. E.g., W_{10} is the world where F is true and G is false, while $W_{0\perp}$ is the world where F is false and G is unknown. Suppose w_{ij} denotes the probability associated with world W_{ij} . Then the possible scope of interaction between F and G can be characterized by the following constraints.

$$\begin{aligned}
\alpha_1 &\leq w_{10} + w_{1\perp} + w_{11} \leq \beta_1 \\
\gamma_1 &\leq w_{00} + w_{0\perp} + w_{01} \leq \delta_1 \\
\alpha_2 &\leq w_{01} + w_{\perp 1} + w_{11} \leq \beta_2 \\
\gamma_2 &\leq w_{00} + w_{\perp 0} + w_{10} \leq \delta_2 \\
w_{ij} &\geq 0, \quad i, j \in \{1, 0, \perp\} \\
\sum_{i,j} w_{ij} &= 1
\end{aligned} \tag{2}$$

The above system of constraints must be satisfied for all modes. Specific constraints for various modes are obtained by adding more constraints to those in Equation (2). In all cases, the confidence levels for $F \wedge G$ and $F \vee G$ are obtained as follows.

$$\begin{aligned}
\text{conf}(F \circ G) = & \langle [\min(\sum_{W_{ij} \models F \circ G} w_{ij}), \max(\sum_{W_{ij} \models F \circ G} w_{ij})], \\
& [\min(\sum_{W_{ij} \not\models F \circ G} w_{ij}), \max(\sum_{W_{ij} \not\models F \circ G} w_{ij})] \rangle
\end{aligned}$$

where $\circ$ is $\wedge$ or $\vee$.

Case 1: Ignorance.

The constraints for ignorance are exactly those in Equation (2). The solution to the above linear program can be shown to be

$$\begin{aligned}
\text{conf}(F \wedge G) &= \langle [\max\{0, \alpha_1 + \alpha_2 - 1\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle, \\
\text{conf}(F \vee G) &= \langle [\max\{\alpha_1, \alpha_2\}, \min\{1, \beta_1 + \beta_2\}], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \min\{\delta_1, \delta_2\}] \rangle.
\end{aligned}$$

The proof is very similar to the proof of a similar result in the context of belief intervals (no doubt) by Ng and Subrahmanian (Ng & Subrahmanian, 1992).

Case 2: Independence.

Independence of events F and G can be characterized by the equation $P(F|G) = P(F)$, where $P(F|G)$ is the conditional probability of the event F given event G . More specifically, since in our model an event can be *true*, *false*, or *unknown*, (in other words, we model belief and doubt independently) we have ⁵:

$$\begin{aligned}
P(F \text{ is true} \mid G \text{ is true}) &= P(F \text{ is true}) \\
P(F \text{ is true} \mid G \text{ is false}) &= P(F \text{ is true}) \\
P(F \text{ is false} \mid G \text{ is true}) &= P(F \text{ is false}) \\
P(F \text{ is false} \mid G \text{ is false}) &= P(F \text{ is false})
\end{aligned} \tag{3}$$

Then the constraints characterizing independence is obtained by adding the following equations to the system of constraints (2).

$$\begin{aligned}
w_{11} &= (w_{10} + w_{1\perp} + w_{11}) \times (w_{01} + w_{\perp 1} + w_{11}) \\
w_{10} &= (w_{10} + w_{1\perp} + w_{11}) \times (w_{00} + w_{\perp 0} + w_{10}) \\
w_{01} &= (w_{00} + w_{0\perp} + w_{01}) \times (w_{01} + w_{\perp 1} + w_{11}) \\
w_{00} &= (w_{00} + w_{0\perp} + w_{01}) \times (w_{00} + w_{\perp 0} + w_{10})
\end{aligned} \tag{4}$$

The belief in $F \wedge_{ind} G$, and doubt in $F \vee_{ind} G$ can be easily verified from the system

⁵ We have nine equations, but it can be shown that the other five are dependent on these four

of constraints 2 and 4 ⁶

$$\begin{array}{rclcl} \alpha_1 \times \alpha_2 & \leq & w_{11} & \leq & \beta_1 \times \beta_2 \\ \gamma_1 \times \gamma_2 & \leq & w_{00} & \leq & \delta_1 \times \delta_2 \end{array} \quad (5)$$

To obtain the doubt in $F \wedge_{ind} G$ we need to compute the minimum and maximum of $w_{00} + w_{0\perp} + w_{01} + w_{10} + w_{\perp 0}$. It is easy to verify that:

$$\gamma_1 + \gamma_2 - \gamma_1 \times \gamma_2 \leq w_{00} + w_{0\perp} + w_{01} + w_{10} + w_{\perp 0} \leq \delta_1 + \delta_2 - \delta_1 \times \delta_2$$

The belief in $F \vee_{ind} G$ is obtained similarly (in the dual manner.) Thus, we have verified that

$$\begin{aligned} \text{conf}(F \wedge_{ind} G) &= \langle [\alpha_1 \times \alpha_2, \beta_1 \times \beta_2], [1 - (1 - \gamma_1) \times (1 - \gamma_2), 1 - (1 - \delta_1) \times (1 - \delta_2)] \rangle. \\ \text{conf}(F \vee_{ind} G) &= \langle [1 - (1 - \alpha_1) \times (1 - \alpha_2), 1 - (1 - \beta_1) \times (1 - \beta_2)], [\gamma_1 \times \gamma_2, \delta_1 \times \delta_2] \rangle. \end{aligned}$$

Case 3: Positive Correlation:

Two events F and G are positively correlated if they overlap as much as possible. This happens when either (i) occurrence of F implies occurrence of G , or (ii) occurrence of G implies occurrence of F . In our framework we model belief and doubt independently, and positive correlation is characterized by 4 possibilities:

- (a) Occurrence of F implies occurrence of G , and non-occurrence of G implies non-occurrence of F .
- (b) Occurrence of F implies occurrence of G , and non-occurrence of F implies non-occurrence of G .
- (c) Occurrence of G implies occurrence of F , and non-occurrence of G implies non-occurrence of F .
- (d) Occurrence of G implies occurrence of F , and non-occurrence of F implies non-occurrence of G .

Each of these four condition sets generates its own equations. For example, (a) can be captured by adding the following equations to the system of constraints 2.

$$\begin{array}{rcl} w_{1\perp} & = & 0 \\ w_{10} & = & 0 \\ w_{\perp 0} & = & 0 \end{array} \quad (6)$$

Hence, for condition (a), the system of constraints 2 becomes

$$\begin{array}{rclcl} \alpha_1 & \leq & w_{11} & \leq & \beta_1 \\ \gamma_1 & \leq & w_{00} + w_{0\perp} + w_{01} & \leq & \delta_1 \\ \alpha_2 & \leq & w_{01} + w_{\perp 1} + w_{11} & \leq & \beta_2 \\ \gamma_2 & \leq & w_{00} & \leq & \delta_2 \\ w_{ij} & \geq & 0, & & i, j \in \{1, 0, \perp\} \\ \sum_{i,j} w_{ij} & = & 1 & & \end{array} \quad (7)$$

The analysis is further complicated by the fact that the confidence levels of

⁶ such *duality* results exist with respect to conjunction and disjunctions lower and upper bounds (and vice versa).

F and G determine which of these cases apply, and it may be different for the lowerbound and upperbound probabilities. For example, if $\alpha_1 > \alpha_2$ ($\beta_1 > \beta_2$), then the lowerbound (upperbound) for belief in $F \wedge_{pc} G$ is obtained when occurrence of F implies occurrence of G . Otherwise, these bounds are obtained when occurrence of G implies occurrence of F .

The solution to these linear programs can be shown to be

$$\begin{aligned} \text{conf}(F \wedge_{pc} G) &= \langle [\min\{\alpha_1, \alpha_2\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \max\{\delta_1, \delta_2\}] \rangle, \text{ and} \\ \text{conf}(F \vee_{pc} G) &= \langle [\max\{\alpha_1, \alpha_2\}, \max\{\beta_1, \beta_2\}], [\min\{\gamma_1, \gamma_2\}, \min\{\delta_1, \delta_2\}] \rangle. \end{aligned}$$

A more intuitive approach to the derivation of confidence levels for conjunction and disjunction of positively correlated events is to rely on the observation that these events overlap to the maximum extent possible. In our framework it means the worlds where F is *true* and those where G is *true* overlap maximally, and hence, one is included in the other. Similarly, since we model belief and doubt independently, the worlds where F is *false* and those where G is *false* also overlap maximally. The combination formulas can be derived directly using these observations.

Case 4: Negative Correlation:

Negative correlation is an appropriate mode to use whenever we know that events F and G overlap as little as possible. This is to be contrasted with positive correlation, where the extent of overlap is the greatest possible. Mutual exclusion, is a special case of negative correlation where the sum of the probabilities of the two events does not exceed 1. In this case the two events do not overlap at all.

In the classical framework, mutual exclusion of two events F and G is characterized by the statement: (i) occurrence of F implies non-occurrence of G , and vice versa. On the other hand, if the two events F and G are negatively correlated but not mutually exclusive, we have: (ii) non-occurrence of F implies occurrence of G , and vice versa. In Case (i) the sum of the probabilities of the two events is at most 1, while in Case (ii) this sum exceeds 1 and hence the two events cannot be mutually exclusive. In our framework we model belief and doubt independently, and each of the above conditions translates to two conditions as follows. Note that in our framework, “not *true*” means “*false* or *unknown*”, and “not *false*” means “*true* or *unknown*”.

Case (i):

- (a) Event F is *true* implies G is not *true*, and vice versa. This condition generates the equation $w_{11} = 0$.
- (b) The dual of condition (a), when the non-occurrence of the two events don't overlap. Event F is *false* implies G is not *false*, and vice versa. This condition generates the equation $w_{00} = 0$.

Case (ii):

- (c) Event F is not *true* implies G is *true*, and vice versa. This condition generates the equations $w_{00} = 0$, $w_{\perp 0} = 0$, $w_{0\perp} = 0$, and $w_{\perp\perp} = 0$.
- (d) The dual of (c), F is not *false* implies G is *false*, and vice versa, which generates the equations $w_{11} = 0$, $w_{\perp 1} = 0$, $w_{1\perp} = 0$, and $w_{\perp\perp} = 0$.

Similar to the case for positive correlation, the confidence levels of F and G determine which of these cases apply. For example, if $\alpha_1 + \alpha_2 > 1$, then case (c) should be used to determine the lowerbound for belief in $F \wedge_{nc} G$.

Alternatively, and more intuitively, we can characterize negative correlation by observing that the worlds where F is *true* and those where G is *true* overlap minimally, and the worlds where F is *false* and those where G is *false* also overlap minimally. The confidences of $F \wedge G$ and $F \vee G$ can be obtained using the equations, or directly from the alternative characterization:

$$\begin{aligned} \text{conf}(F \wedge_{nc} G) &= \langle [\max\{0, \alpha_1 + \alpha_2 - 1\}, \max\{0, \beta_1 + \beta_2 - 1\}], [\min\{1, \gamma_1 + \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle \\ \text{conf}(F \vee_{nc} G) &= \langle [\min\{1, \alpha_1 + \alpha_2\}, \min\{1, \beta_1 + \beta_2\}], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \max\{0, \delta_1 + \delta_2 - 1\}] \rangle \end{aligned}$$

Case 5: Mutual Exclusion:

Mutual exclusion is a special case of negative correlation. The main difference is that it requires the sum of the two probabilities to be at most 1, which is not necessarily the case for negative correlation (see the previous case). In the classical framework, if two events are mutually exclusive, their negation are not necessarily mutually exclusive. Rather, they are negatively correlated. In our framework, however, one or both conditions (a) and (b), discussed in the previous case, can hold. The appropriate condition is determined by the confidence levels of the two mutually exclusive events, and the corresponding combination formula can be obtained from the combination formulas of negative correlation. The following formulas, for example, are for mutually exclusive events F and G where $\alpha_1 + \alpha_2 \leq \beta_1 + \beta_2 \leq 1$ (but no other restriction).

$$\begin{aligned} \text{conf}(F \wedge_{me} G) &= \langle [0, 0], [\min\{1, \gamma_1 + \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle. \\ \text{conf}(F \vee_{me} G) &= \langle [\alpha_1 + \alpha_2, \beta_1 + \beta_2], [\max\{0, \gamma_1 + \gamma_2 - 1\}, \max\{0, \delta_1 + \delta_2 - 1\}] \rangle. \end{aligned}$$

■

Next, we show that the combination formulas for various modes preserve consistent as well as reduced confidence levels. The case for reduced confidence levels is more involved and will be presented first. The other case is similar, for which we only state the theorem.

Theorem 4.2

Suppose F and G are any formulas and assume their confidence levels are reduced (Definition 4.3). Then the confidence levels of the formulas $F \wedge G$ and $F \vee G$, obtained under the various modes above are all reduced.

Proof. Let $\text{conf}(F) = \langle [\alpha_1, \beta_1], [\gamma_1, \delta_1] \rangle$ and $\text{conf}(G) = \langle [\alpha_2, \beta_2], [\gamma_2, \delta_2] \rangle$. Since the confidence levels of F and G are reduced, we have:

$$\begin{aligned} 0 &\leq \alpha_i \leq \beta_i \leq 1 \\ 0 &\leq \gamma_i \leq \delta_i \leq 1 \\ \alpha_i + \delta_i &\leq 1 \\ \beta_i + \gamma_i &\leq 1 \end{aligned}$$

The consistency of the confidence levels of the combination events $F \wedge G$ and $F \vee G$

in different modes as derived in Theorem 4.1 follow from the above constraints. For example let us consider

$$\text{conf}(A \wedge_{ig} B) = \langle [\max\{0, \alpha_1 + \alpha_2 - 1\}, \min\{\beta_1, \beta_2\}], [\max\{\gamma_1, \gamma_2\}, \min\{1, \delta_1 + \delta_2\}] \rangle$$

We need to show

- (1) $\max\{0, \alpha_1 + \alpha_2 - 1\} \leq \min\{\beta_1, \beta_2\}$
- (2) $\max\{\gamma_1, \gamma_2\} \leq \min\{1, \delta_1 + \delta_2\}$
- (3) $\max\{0, \alpha_1 + \alpha_2 - 1\} + \min\{1, \delta_1 + \delta_2\} \leq 1$
- (4) $\min\{\beta_1, \beta_2\} + \max\{\gamma_1, \gamma_2\} \leq 1$

To prove (1): If $\max\{0, \alpha_1 + \alpha_2 - 1\} = 0$ then (1) holds. Otherwise, assume, without loss of generality, that $\min\{\beta_1, \beta_2\} = \beta_1$. We can write

$$\begin{aligned} \alpha_1 &\leq \beta_1 \\ \alpha_2 &\leq 1 \end{aligned}$$

and hence

$$\alpha_1 + \alpha_2 \leq \beta_1 + 1$$

and (1) follows.

Inequality (2) follows easily from $\gamma_i \leq \delta_i \leq 1$.

To prove (3): If $\max\{0, \alpha_1 + \alpha_2 - 1\} = 0$ then (3) holds. Otherwise, we can write

$$\begin{aligned} \alpha_1 + \delta_1 &\leq 1 \\ \alpha_2 + \delta_2 &\leq 1 \end{aligned}$$

and hence

$$\alpha_1 + \alpha_2 - 1 + \delta_1 + \delta_2 \leq 1$$

and (3) follows. Note that if $\delta_1 + \delta_2 > 1$ then $\alpha_1 + \alpha_2 - 1 + 1 \leq 1$ follows from the above constraint.

To prove (4) let $\min\{\beta_1, \beta_2\} = \beta_j$ and $\max\{\gamma_1, \gamma_2\} = \gamma_k$ where $j, k \in \{1, 2\}$. Then $\beta_j + \gamma_k \leq \beta_k + \gamma_k \leq 1$.

Proving the consistency of the confidence levels of other combinations and other modes are similar and will not be elaborated here. ■

Theorem 4.3

Suppose F and G are any formulas and assume their confidence levels are consistent (Definition 4.2). Then the confidence levels of the formulas $F \wedge G$ and $F \vee G$, obtained under the various modes above are all consistent.

Proof. Proof is similar to the previous theorem and is omitted. ■

5 Probabilistic Deductive Databases

In this section, we develop a framework for probabilistic deductive databases using a language of probabilistic programs (p-programs). We make use of the probabilistic calculus developed in Section 4 and develop the syntax and declarative semantics for programming with confidence levels. We also provide the fixpoint semantics of programs in this framework and establish its equivalence to the declarative semantics. We will use the first-order language **L** of Section 4 as the underlying logical language in this section.

Syntax of p-Programs: A *rule* is an expression of the form $A \stackrel{c}{\leftarrow} B_1, \dots, B_m, m \geq 0$, where A, B_i are atoms and $c \equiv \langle [\alpha, \beta], [\gamma, \delta] \rangle$ is the confidence level associated with the rule⁷. When $m = 0$, we call this a *fact*. All variables in the rule are assumed to be universally quantified outside the whole rule, as usual. We restrict attention to range restricted rules, as is customary. A *probabilistic rule* (p-rule) is a triple $(r; \mu_r, \mu_p)$, where r is a rule, μ_r is a mode indicating how to conjoin the confidence levels of the subgoals in the body of r (and with that of r itself), and μ_p is a mode indicating how the confidence levels of different derivations of an atom involving the head predicate of r are to be disjoined. We say μ_r (μ_p) is the mode associated with the body (head) of r , and call it the *conjunctive* (*disjunctive*) mode. We refer to r as the underlying rule of this p-rule. When r is a fact, we omit μ_r for obvious reasons. A *probabilistic program* (p-program) is a finite collection of p-rules such that whenever there are p-rules whose underlying rules define the same predicate, the mode associated with their head is identical. This last condition ensures different rules defining the same predicate q agree on the manner in which confidences of identical q -atoms generated by these rules are to be combined. The notions of Herbrand universe H_P and Herbrand base B_P associated with a p-program P are defined as usual. A p-rule is ground exactly when every atom in it is ground. The Herbrand instantiation P^* of a p-program is defined in the obvious manner. The following example illustrates our framework.

Example 5.1

People are assessed to be at high risk for various diseases, depending on factors such as age group, family history (with respect to the disease), etc. Accordingly, high risk patients are administered appropriate medications, which are prescribed by doctors among several alternative ones. Medications cause side effects, sometimes harmful ones, leading to other symptoms and diseases⁸. Here, the extent of risk, administration of medications⁹, side effects (caused by medications), and prognosis are all uncertain phenomena, and we associate confidence levels with them. The following program is a sample of the uncertain knowledge related to these phenomena.

1. $(high-risk(X, D) \stackrel{\langle [0.65, 0.65], [0.1, 0.1] \rangle}{\leftarrow} midaged(X), family-history(X, D); ind, _).$
2. $(takes(X, M) \stackrel{\langle [0.40, 0.40], [0, 0] \rangle}{\leftarrow} high-risk(X, D), medication(D, M); ign, _).$
3. $(prognosis(X, D) \stackrel{\langle [0.70, 0.70], [0.12, 0.12] \rangle}{\leftarrow} high-risk(X, D); ign, pc).$
4. $(prognosis(X, D) \stackrel{\langle [0.20, 0.20], [0.70, 0.70] \rangle}{\leftarrow} takes(X, M), side-effects(M, D); ind, pc).$

We can assume an appropriate set of facts (the EDB) in conjunction with the above program. For rule 1, it is easy to see that each ground atom involving the predicate *high-risk* has at most one derivation. Thus, a disjunctive mode for this

⁷ We assume only consistent confidence levels henceforth (see Section 4).

⁸ Recent studies on the effects of certain medications on high risk patients for breast cancer provide one example of this.

⁹ Uncertainty in this is mainly caused by the choices available and the fact that even under identical conditions doctors need not prescribe the same drug. The probabilities here can be derived from statistical data on the relative frequency of prescriptions of drugs under given conditions.

rule will be clearly redundant, and we have suppressed it for convenience. A similar remark holds for rule 2. Rule 1 says that if a person is midaged and the disease D has struck his ancestors, then the confidence level in the person being at high risk for D is given by propagating the confidence levels of the body subgoals and combining them with the rule confidence in the sense of $\wedge_{ind}$. This could be based on an expert's belief that the factors *midaged* and *family-history* contributing to high risk for the disease are independent. Each of the other rules has a similar explanation. For the last rule, we note that the potential of a medication to cause side effects is an intrinsic property independent of whether one takes the medication. Thus the conjunctive mode used there is independence. Finally, note that rules 3 and 4, defining *prognosis*, use positive correlation as a conservative way of combining confidences obtained from different derivations. For simplicity, we show each interval in the above rules as a point probability. Still, note that the confidences for atoms derived from the program will be genuine intervals. ■

A Valuation Based Semantics: We develop the declarative semantics of p-programs based on the notion of valuations. Let P be a p-program. A *probabilistic valuation* is a function $v : B_P \rightarrow \mathcal{L}_c$ which associates a confidence level with each ground atom in B_P . We define the satisfaction of p-programs under valuations, with respect to the truth order $\leq_t$ of the trilattice (see Section 4)¹⁰. We say a valuation v *satisfies* a ground p-rule $\rho \equiv (A \stackrel{c}{\leftarrow} B_1, \dots, B_m; \mu_r, \mu_p)$, denoted $\models_v \rho$, provided $c \wedge_{\mu_r} v(B_1) \wedge_{\mu_r} \dots \wedge_{\mu_r} v(B_m) \leq_t v(A)$. The intended meaning is that in order to satisfy this p-rule, v must assign a confidence level to A that is no less true (in the sense of $\leq_t$) than the result of the conjunction of the confidences assigned to B_i 's by v and the rule confidence c , in the sense of the mode μ_r . Even when a valuation satisfies (all ground instances of) each rule in a p-program, it may not satisfy the p-program as a whole. The reason is that confidences coming from different derivations of atoms are combined strengthening the overall confidence. Thus, we need to impose the following additional requirement.

Let $\rho \equiv (r \equiv A \stackrel{c}{\leftarrow} B_1, \dots, B_m; \mu_r, \mu_p)$ be a ground p-rule, and v a valuation. Then we denote by $rule-conf(A, \rho, v)$ the confidence level propagated to the head of this rule under the valuation v and the rule mode μ_r , given by the expression $c \wedge_{\mu_r} v(B_1) \wedge_{\mu_r} \dots \wedge_{\mu_r} v(B_m)$. Let $P^* = P_1^* \cup \dots \cup P_k^*$ be the partition of P^* such that (i) each P_i^* contains all (ground) p-rules which define the same atom, say A_i , and (ii) A_i and A_j are distinct, whenever $i \neq j$. Suppose μ_i is the mode associated with the head of the p-rules in P_i^* . We denote by $atom-conf(A_i, P, v)$ the confidence level determined for the atom A_i under the valuation v using the program P . This is given by the expression $\vee_{\mu_i} \{rule-conf(A_i, \rho, v) | \rho \in P_i^*\}$. We now define satisfaction of p-programs.

Definition 5.1

Let P be a p-program and v a valuation. Then v satisfies P , denoted $\models_v P$ exactly

¹⁰ Satisfaction can be defined with respect to each of the 3 orders of the trilattice, giving rise to different interesting semantics. Their discussion is beyond the scope of this paper.

when v satisfies each (ground) p-rule in P^* , and for all atoms $A \in B_P$, $atom-conf(A, P, v) \leq_t v(A)$.

The additional requirement ensures the valuation assigns a strong enough confidence to each atom so it will support the combination of confidences coming from a number of rules (pertaining to this atom). A p-program P logically implies a p-fact $A \xleftarrow{c}$, denoted $P \models A \xleftarrow{c}$, provided every valuation satisfying P also satisfies $A \xleftarrow{c}$. We next have

Proposition 5.1

Let v be a valuation and P a p-program. Suppose the mode associated with the head of each p-rule in P is positive correlation. Then $\models_v P$ iff v satisfies each rule in P^* .

Proof. We shall show that if $rule-conf(A, \rho_i, v) \leq_t v(A)$ for all rules ρ_i defining a ground atom A , then $atom-conf(A, P, v) \leq_t v(A)$, where the disjunctive mode for A is positive correlation. This follows from the formula for $\vee_{pc}$, obtained in Theorem 4.1. It is easy to see that $c_1 \vee_{pc} c_2 = c_1 \oplus_t c_2$. But then, $rule-conf(A, \rho_i, v) \leq_t v(A)$ implies that $\oplus_t \{rule-conf(A, \rho_i, v)\} \leq_t v(A)$ and hence $atom-conf(A, P, v) \leq_t v(A)$. ■

The above proposition shows that when positive correlation is the only disjunctive mode used, satisfaction is very similar to the classical case.

For the declarative semantics of p-programs, we need something like the “least” valuation satisfying the program. It is straightforward to show that the class of all valuations Υ from B_P to $\mathcal{L}_c$ itself forms a trilattice, complete with all the 3 orders and the associated meets and joins. They are obtained by a pointwise extension of the corresponding order/operation on the trilattice $\mathcal{L}_c$. We give one example. For valuations u, v , $u \leq_t v$ iff $\forall A \in B_P$, $u(A) \leq_t v(A)$; $\forall A \in B_P$, $(u \otimes_t v)(A) = u(A) \otimes_t v(A)$. One could investigate “least” with respect to each of the 3 orders of the trilattice. In this paper, we confine attention to the order $\leq_t$. The least (greatest) valuation is then the valuation **false** (**true**) which assigns the confidence level $\perp_t$ ($\top_t$) to every ground atom. We now have

Lemma 5.1

Let P be any p-program and u, v be any valuations satisfying P . Then $u \otimes_t v$ is also a valuation satisfying P . In particular, $\otimes_t \{v \mid \models_v P\}$ is the least valuation satisfying P .

Proof. We prove this in two steps. First, we show that for any ground p-rule

$$\rho \equiv (r \equiv A \xleftarrow{c} B_1, \dots, B_m; \mu_r, \mu_p)$$

whenever valuations u and v satisfy ρ , so does $u \otimes_t v$. Secondly, we shall show that for a p-program P , whenever $atom-conf(A, P, u) \leq_t u(A)$ and $atom-conf(A, P, v) \leq_t v(A)$, then we also have $atom-conf(A, P, u \otimes_t v) \leq_t u \otimes_t v(A)$. The lemma will follow from this.

(1) Suppose $u \models \rho$ and $v \models \rho$. We prove the case where the conjunctive mode μ_r associated with this rule is ignorance. The other cases are similar. It is straightforward to verify the following.

- (i) $u \otimes_t v(B_1) \wedge_{ig} \cdots \wedge_{ig} u \otimes_t v(B_m) \leq_t u(B_1) \wedge_{ig} \cdots \wedge_{ig} u(B_m) \leq_t u(A)$.
- (ii) $u \otimes_t v(B_1) \wedge_{ig} \cdots \wedge_{ig} u \otimes_t v(B_m) \leq_t v(B_1) \wedge_{ig} \cdots \wedge_{ig} v(B_m) \leq_t v(A)$.

From (i) and (ii), we have $u \otimes_t v(B_1) \wedge_{ig} \cdots \wedge_{ig} u \otimes_t v(B_m) \leq_t u \otimes_t v(A)$, showing $u \otimes_t v \models \rho$.

(2) Suppose u, v are any two valuations satisfying a p-program P . Let $\rho_1, \dots, \rho_n$ be the set of all ground p-rules in P^* whose heads are A . Let $c_i = \text{rule-conf}(A, \rho_i, u)$ and $d_i = \text{rule-conf}(A, \rho_i, v)$. Since $u \models P$ and $v \models P$, we have that $\bigvee_{\mu_p}(c_i \mid 1 \leq i \leq n) \leq_t u(A)$ and $\bigvee_{\mu_p}(d_i \mid 1 \leq i \leq n) \leq_t v(A)$, where μ_p is the disjunctive mode associated with A . Again, we give the proof for the case μ_p is ignorance as the other cases are similar. Let $e_i = \text{rule-conf}(A, \rho_i, u \otimes_t v)$, $1 \leq i \leq n$. Clearly, $e_i \leq_t c_i$ and $e_i \leq_t d_i$. Thus, $\bigvee_{\mu_p}(e_i \mid 1 \leq i \leq n) \leq_t \bigvee_{\mu_p}(c_i \mid 1 \leq i \leq n) \leq_t u(A)$ and $\bigvee_{\mu_p}(e_i \mid 1 \leq i \leq n) \leq_t \bigvee_{\mu_p}(d_i \mid 1 \leq i \leq n) \leq_t v(A)$. It then follows that $\bigvee_{\mu_p}(e_i \mid 1 \leq i \leq n) \leq_t u(A) \otimes_t v(A) = u \otimes_t v(A)$, which was to be shown. ■

We take the least valuation satisfying a p-program as characterizing its declarative semantics.

Example 5.2

Consider the following p-program P .

1. $(A \xleftarrow{\langle [0.5, 0.7], [0.3, 0.45] \rangle} B; \text{ind}, pc).$
2. $(A \xleftarrow{\langle [0.6, 0.8], [0.1, 0.2] \rangle} C; \text{ign}, pc).$
3. $(B \xleftarrow{\langle [0.9, 0.95], [0, 0.1] \rangle} ; -, \text{ind}).$
4. $(C \xleftarrow{\langle [0.7, 0.8], [0.1, 0.2] \rangle} ; -, \text{ind}).$

In the following we show three valuations v_1, v_2, v_3 , of which v_1 and v_3 satisfy P , while v_2 does not. In fact, v_3 is the least valuation satisfying P .

val	B	C	A
v_1	$\langle [0.9, 1], [0, 0] \rangle$	$\langle [0.8, 0.9], [0.05, 0.1] \rangle$	$\langle [0.5, 0.9], [0, 0] \rangle$
v_2	$\langle [0.9, 1], [0, 0] \rangle$	$\langle [0.9, 1], [0, 0] \rangle$	$\langle [0.5, 0.7], [0.1, 0.4] \rangle$
v_3	$\langle [0.9, 0.95], [0, 0.1] \rangle$	$\langle [0.7, 0.8], [0.1, 0.2] \rangle$	$\langle [0.45, 0.8], [0.1, 0.4] \rangle$

For example, consider v_1 . It is easy to verify that v_1 satisfies P . Rules 1 through 4 are satisfied by v_1 since:

$$\begin{aligned}
& \langle [0.5, 0.7], [0.3, 0.45] \rangle \wedge_{ind} \langle [0.9, 1], [0, 0] \rangle = \langle [0.45, 0.7], [0, 0] \rangle \leq_t \langle [0.5, 0.9], [0, 0] \rangle \\
& \langle [0.6, 0.8], [0.1, 0.2] \rangle \wedge_{ign} \langle [0.8, 0.9], [0.05, 0.1] \rangle = \\
& \quad \langle [0.4, 0.8], [0.1, 0.3] \rangle \leq_t \langle [0.5, 0.9], [0, 0] \rangle \\
& \langle [0.9, 0.95], [0, 0.1] \rangle \leq_t \langle [0.9, 1], [0, 0] \rangle \\
& \langle [0.7, 0.8], [0.1, 0.2] \rangle \leq_t \langle [0.8, 0.9], [0.05, 0.1] \rangle
\end{aligned}$$

Further, the confidence level of A computed by the combination of rules 1 and 2 is also satisfied by v_1 , namely,

$$\begin{aligned}
& (\langle [0.5, 0.7], [0.3, 0.45] \rangle \wedge_{ind} \langle [0.9, 1], [0, 0] \rangle) \vee_{pc} (\langle [0.6, 0.8], [0.1, 0.2] \rangle \\
& \quad \wedge_{ign} \langle [0.8, 0.9], [0.05, 0.1] \rangle) = \langle [0.45, 0.8], [0, 0] \rangle \leq_t \langle [0.5, 0.9], [0, 0] \rangle
\end{aligned}$$

Fixpoint Semantics: We associate an “immediate consequence” operator T_P with a p-program P , defined as follows.

Definition 5.2

Let P be a p-program and P^* its Herbrand instantiation. Then T_P is a function

$T_P : \Upsilon \rightarrow \Upsilon$, defined as follows. For any probabilistic valuation v , and any ground atom $A \in B_P$, $T_P(v)(A) = \vee_{\mu_p} \{c_A \mid \text{there exists a p-rule } (A \xleftarrow{c} B_1, \dots, B_m, \mu_r, \mu_p) \in P^*, \text{ such that } c_A = c \wedge_{\mu_r} v(B_1) \wedge_{\mu_r} \dots \wedge_{\mu_r} v(B_m)\}$.

Call a valuation v *consistent* provided for every atom A , $v(A)$ is consistent, as defined in Section 3.

Theorem 5.1

(1) T_P always maps consistent valuations to consistent valuations. (2) T_P is monotone and continuous.

Proof. (1) This fact follows Theorem 4.3, where we have shown that the combination functions for all modes map consistent confidence levels to consistent confidence levels. (2) This follows from the fact that the combination functions for all modes are themselves monotone and continuous. ■

We define bottom-up iterations based on T_P in the usual manner.

$T_P \uparrow 0 = \mathbf{false}$ (which assigns the truth-value $\perp_t$ to every ground atom).

$T_P \uparrow \alpha = T_P(T_P \uparrow \alpha - 1)$, for a successor ordinal α .

$T_P \uparrow \alpha = \oplus_t \{T_P \uparrow \beta \mid \beta < \alpha\}$, for a limit ordinal α .

We have the following results.

Proposition 5.2

Let v be any valuation and P be a p-program. Then v satisfies P iff $T_P(v) \leq_t v$.

Proof. (*only if*). If v satisfies P , then by Definition 5.1, for all atoms $A \in B_P$, $\text{atom-conf}(A, P, v) \leq_t v(A)$ and hence $T_P(v) \leq_t v$.

(*if*). If $T_P(v) \leq_t v$, then by the definition of T_P (Definition 5.2) for all atoms $A \in B_P$, $\text{atom-conf}(A, P, v) \leq_t v(A)$ and hence v satisfies P . ■

The following theorem is the analogue of the van Emden-Kowalski theorem for classical logic programming.

Theorem 5.2

Let P be a p-program. Then the following claims hold.

(i) $\text{lf}p(T_P) = \otimes_t \{v \mid v \models_v P\} = \text{the } \leq_t\text{-least valuation satisfying } P$.

(ii) For a ground atom A , $\text{lf}p(T_P)(A) = c$ iff $P \models A \xleftarrow{c}$.

Proof. Follows Lemma 5.1, Theorem 5.1 and Proposition 5.2. Proof is similar to the analogous theorem of logic programming and details are omitted. ■

6 Proof Theory

Since confidences coming from different derivations of a fact are combined, we need a notion of disjunctive proof-trees. We note that the notions of substitution, unification, etc. are analogous to the classical ones. A variable appearing in a rule is *local* if it only appears in its body.

Definition 6.1

Let G be a(n atomic) goal and P a p-program. Then a *disjunctive proof-tree* (DPT) for G with respect to P is a tree T defined as follows.

1. T has two kinds of nodes: *rule* nodes and *goal* nodes. Each rule node is labeled by a rule in P and a substitution. Each goal node is labeled by an atomic goal. The root is a goal node labeled G .
2. Let u be a goal node labeled by an atom A . Then every child (if any) of u is a rule node labeled (r, θ) , where r is a rule in P whose head is unifiable with A using the mgu θ . We assume that each time a rule r appears in the tree, its variables are renamed to new variables that do not appear anywhere else in the tree. Hence r in the label (r, θ) actually represents a renamed instance of the rule.
3. If u is a rule node labeled (r, θ) , then whenever an atom B occurs in the body of $r' = r\theta$, u has a goal child v labeled B .
4. For any two substitutions π, θ occurring in T , $\pi(V) = \theta(V)$, for every variable V . In other words, all substitutions occurring in T are compatible.

A node without children is called a leaf. A *proper* DPT is a finite DPT T such that whenever T has a goal leaf labeled A , there is no rule in P whose head is unifiable with A . We only consider proper DPTs unless otherwise specified. A rule leaf is a *success* node (represents a database fact) while a goal leaf is a *failure* node.

Remarks:

- (1) The definition of disjunctive proof tree captures the idea that when working with uncertain information in the form of probabilistic rules and facts, we need to consider the disjunction of all proofs in order to determine the best possible confidence in the goal being proved.
- (2) However, notice that the definition does *not* insist that a goal node A should have rule children corresponding to all possible unifiable rules and mgu's.
- (3) We assume without loss of generality that all rules in the p-program are standardized apart by variable renaming so they share no common variables.
- (4) A goal node can have several rule children corresponding to the same rule. That is, a goal node can have children labeled $(r, \theta_1), \dots, (r, \theta_n)$, where r is (a renamed version of) a rule in the program. But we require that $r'_i = r\theta_i$, $i = 1, \dots, n$, be distinct.
- (5) We require all substitutions in the tree to be compatible. The convention explained above ensures there will be no conflict among them on account of common variables across rules (or different invocations of the same rule).
- (6) Note that a DPT can be finite or infinite.
- (7) In a proper DPT, goal leaves are necessarily failure nodes; this is not true in non-proper DPTs.
- (8) A proper DPT with no failure nodes has only rule leaves, hence, it has an odd height.

Confidences are associated with (finite) DPTs as follows.

Definition 6.2

Let P be a p-program, G a goal, and T any finite DPT for G with respect to P .

We associate confidences with the nodes of T as follows.

1. Each failure node gets the confidence $\langle [0, 0], [1, 1] \rangle$, the **false** confidence level with respect to truth ordering, $\perp_t$ (see Section 3). Each success node labeled (r, θ) , where r is a rule in P , and c is the confidence of rule r , gets the confidence c .
2. Suppose u is a rule node labeled (r, θ) , such that the confidence of r is c , its (conjunctive) mode is μ_r , and the confidences of the children of u are $c_1, \dots, c_m$. Then u gets the confidence $c \wedge_{\mu_r} c_1 \wedge_{\mu_r} \dots \wedge_{\mu_r} c_m$.
3. Suppose u is a goal node labeled A , with a (disjunctive) mode μ_p such that the confidences of its children are $c_1, \dots, c_k$. Then u gets the confidence $c_1 \vee_{\mu_p} \dots \vee_{\mu_p} c_k$.

We recall the notions of identity and annihilator from algebra (*e.g.* see Ullman (Ullman, 1989)). Let $c \in \mathcal{L}_c$ be any element of the confidence lattice and $\odot$ be any operation of the form $\wedge_\mu$ or of the form $\vee_\mu$, μ being any of the modes discussed in Section 4. Then c is an *identity* with respect to $\odot$, if $\forall d \in \mathcal{L}_c, c \odot d = d \odot c = d$. It is an *annihilator* with respect to $\odot$, if $\forall d \in \mathcal{L}_c, c \odot d = d \odot c = c$. The proof of the following proposition is straightforward.

Proposition 6.1

The truth-value $\perp_t = \langle [0, 0], [1, 1] \rangle$ is an identity with respect to disjunction and an annihilator with respect to conjunction. The truth-value $\top_t = \langle [1, 1], [0, 0] \rangle$ is an identity with respect to conjunction and an annihilator with respect to disjunction. These claims hold for all modes discussed in Section 4.

In view of this proposition, we can consider only DPTs without failure nodes without losing any generality.

We now proceed to prove the soundness and completeness theorems. First, we need some definitions.

Definition 6.3

A *branch* B of a DPT T is a set of nodes of T , defined as follows. The root of T belongs to B . Whenever a goal node is in B , exactly one of its rule children (if any) belongs to B . Finally, whenever a rule node belongs to B , all its goal children belong to B . We extend this definition to the subtrees of a DPT in the obvious way. A *subbranch* of T rooted at a goal node G is the branch of the subtree of T rooted at G .

We can associate a substitution with a (sub)branch B as follows. (1) The substitution associated with a success node labeled (r, θ) is just θ . (2) The substitution associated with an internal goal node is simply the substitution associated with its unique rule child in B . (3) The substitution associated with an internal rule node u in B which is labeled (r, θ) is the composition of θ and the substitutions associated with the goal children of u .

The substitution associated with a branch is that associated with its root.

We say a DPT T is *well-formed* if it satisfies the following conditions: (i) T is proper, (ii) For every goal node G in T , for any two (sub)branches B_1, B_2 of T rooted at G , the substitutions associated with B_1 and B_2 are distinct.

The second condition ensures no two branches correspond to the same classical “proof” of the goal or a sub-goal. Without this condition, since the probabilistic

conjunctions and disjunctions are not idempotent, the confidence of the same proof could be wrongly combined giving an incorrect confidence for the (root of the) DPT.

Henceforth, we will only consider well-formed DPTs, namely, DPTs that are proper, have no failure nodes, and have distinct substitutions for all (sub) branches corresponding to a goal node, for all goal nodes.

Theorem 6.1 (Soundness)

Let P be a p-program and G a (ground) goal. If there is a finite well-formed DPT for G with respect to P with an associated confidence c at its root, then $c \leq_t lfp(T_P)(G)$.

Proof. First, we make the following observations regarding the combination functions of Theorem 4.1:

- (1) Conjunctive combination functions (all modes) are monotone.
- (2) Disjunctive combination functions (all modes) are monotone.
- (3) If F and G are confidence levels, then $conf(F \wedge_\mu G) \leq_t conf(F)$ and $conf(F) \leq_t conf(F \vee_\mu G)$ for all conjunctive and disjunctive combination functions (all modes).

We prove the soundness theorem by induction on the height of the DPT. Assume the well-formed DPT T of height h is for the goal G . Note that T has an odd height, $h = 2k - 1$ for some $k \geq 1$, since it is a proper DPT with no failure nodes (see Remark 7 at the beginning of this section).

Basis: $k = 1$. In this case the DPT consists of the goal root labeled G and one child labeled (r, θ) , where r is a rule in P whose head is unifiable with G . Note that this child node is a success leaf. *i.e.* it represents a fact. Obviously, in the first iteration of T_P , $conf(G) = c_r$, where c_r is the confidence level of r . It follows from the monotonicity of T_P , that $c = c_r \leq_t lfp(T_P)(G)$.

Induction: $k > 1$. Assume the inductive hypothesis holds for every DPT of height $h' = 2k' - 1$, where $k' < k$. Consider the DPT T for G . The root G has rule children R_i labeled (r_i, θ_i) . Each R_i is either a fact, or has goal children $G_{i_1}, \dots, G_{i_{n_i}}$. Consider the subtrees of T rooted at these goal grand children of G . By the inductive hypothesis, the confidence levels c_{i_j} associated with the goal grand children G_{i_j} by the DPT are less than or equal to their confidence levels calculated by T_P , *i.e.* , $c_{i_j} \leq_t lfp(T_P)(G_{i_j})$. Hence, by properties (1)-(3) above, the confidence level associated to G by T is less than or equal to the confidence level of G obtained by another application of T_P , $c \leq_t T_P(lfp(T_P))(G)$. Hence $c \leq_t lfp(T_P)(G)$. Note that T must be well-formed otherwise this argument is not valid. ■

Theorem 6.2 (Completeness)

Let P be a p-program and G a goal such that for some number $k < \omega$, $lfp(T_P)(G) = T_P \uparrow k(G)$. Then there is a finite DPT T for G with respect to P with an associated confidence c at its root, such that $lfp(T_P)(G) \leq_t c$.

Proof. Let k be the smallest number such that $T_P \uparrow k(G) = lfp(T_P)(G)$. We shall show by induction on k that there is a DPT T for G with respect to P such that the confidence computed by it is at least $lfp(T_P)(G)$.

Basis: $k = 0$. This implies $lfp(T_P)(G) = \langle [0, 0], [1, 1] \rangle$. This case is trivial. The DPT consists of a failure node labeled G .

Induction: Suppose the result holds for a certain number n . We show that it also holds for $n + 1$. Suppose A is a ground atom such that $lfp(T_P)(A) = c = T_P \uparrow n + 1(A)$. Now, $T_P \uparrow n + 1(A) = \bigvee_{\mu_p} \{c_r \wedge_{\mu_r} T_P \uparrow n(B_1) \wedge_{\mu_r} \dots \wedge_{\mu_r} T_P \uparrow n(B_m)\}$. There exists a rule r such that μ_r is the mode associated with its body, and μ_p is the mode associated with its head, and there exists a ground substitution θ such that $r\theta \equiv A \stackrel{c_r}{\leftarrow} B_1, \dots, B_m$.

Consider the DPT for A obtained as follows. Let the root be labeled A . The root has a rule child corresponding to each rule instance used in the above computation of $T_P \uparrow n + 1(A)$. Let v be a rule child created at this step, and suppose $A \stackrel{c_r}{\leftarrow} B_1, \dots, B_m$ is the rule instance corresponding to it and let θ be the substitution used to unify the head of the original rule with the atom A . Then v has m goal children with labels $B_1, \dots, B_m$ respectively. Finally, by induction hypothesis, we can assume that (i) a DPT for B_i is rooted at the node labeled B_i , and (ii) the confidence computed by this latter tree is at least $lfp(T_P)(B_i) = T_P \uparrow n(B_i)$, $1 \leq i \leq m$. In this case, it readily follows from the definition of the confidence computed by a proof-tree that the confidence computed by T is at least $\bigvee_{\mu_p} \{c_r \wedge_{\mu_r} conf(body(r)) \mid r \text{ is a rule defining } A, c_r \text{ is the confidence associated with it, } \mu_r \text{ is the mode associated with its head, and } \mu_p \text{ is the mode associated with its body}\}$.

But this confidence is exactly $T_P \uparrow n + 1(A)$. The induction is complete and the theorem follows. $\blacksquare$

Theorems 6.1 and 6.2 together show that the confidence of an arbitrary ground atom computed according to the fixpoint semantics and using an appropriate disjunctive proof tree is the same. This in turn is the same as the confidence associated according to the (valuation based) declarative semantics. In particular, as we will discuss in Section 7, when the disjunctive mode associated with all recursive predicates is positive correlation, the theorems guarantee that the exact confidence associated with the goal can be effectively computed by constructing an appropriate finite DPT (according to Theorem 6.2) for it. Even when these modes *are* used indiscriminately, we can still obtain the confidence associated with the goal with an arbitrarily high degree of accuracy, by constructing DPTs of appropriate height.

7 Termination and Complexity

In this section, we first compare our work with that of Ng and Subrahmanian (Ng & Subrahmanian, 1992; Ng & Subrahmanian, 1993) (see Section 1 for a general comparison with non-probabilistic frameworks). First, let us examine the (only) “mode” for disjunction used by them¹¹. They combine the confidences of an atom A coming from different derivations by taking their intersection. Indeed, the bottom of their lattice is a valuation (called “formula function” there) that assigns the

¹¹ Their framework allows an infinite class of “conjunctive modes”. Also, recall they represent only beliefs.

interval $[0, 1]$ to every atom. From the trilattice structure, it is clear that (i) their bottom corresponds to $\perp_p$, and (ii) their disjunctive mode corresponds to $\oplus_p$.

Example 7.1

- $r_1: p(X, Y) : [V_1 \times V_3, V_2 \times V_4] \leftarrow e(X, Z) : [V_1, V_2], \quad p(Z, Y) : [V_3, V_4].$
- $r_2: p(X, Y) : [V_1, V_2] \leftarrow e(X, Y) : [V_1, V_2].$
- $r_3: e(1, 2) : [1, 1].$
- $r_4: e(1, 3) : [1, 1].$
- $r_5: e(3, 2) : [0.9, 0.9].$

This is a pf-program in the framework of Ng and Subrahmanian (Ng & Subrahmanian, 1993). In a pf-rule each literal is annotated by an interval representing the lower-bound and upper-bound of belief¹². Variables can appear in the annotations, and the annotation of the head predicate is usually a function of body literals annotations. The program in this example is basically the transitive closure program, with independence as the conjunctive mode in the first rule. The disjunctive function for the p predicate, as explained above, is interval intersection. Let us denote the operator T_P defined by them as T_P^{NS} for distinguishing it from ours. It is not hard to see that this program is inconsistent in their framework, and $lfp(T_P^{NS})$ would assign an empty probability range for $p(1, 2)$. This is due to the existence of two derivations for $p(1, 2)$, with non-overlapping intervals. This is quite unintuitive. Indeed, there is a definite path (with probability 1) corresponding to the edge $e(1, 2)$. One may wonder whether it makes sense to compare this approach with ours on an example program which is inconsistent according to their semantics. The point is that in this example, there is a certain path with probability $[1, 1]$ from 1 to 2, and an approach that regards this program as inconsistent is not quite intuitive.

Now, consider the p-program corresponding to the annotated program $\{r_1, \dots, r_5\}$, obtained by stripping off atom annotations in r_1, r_2 and shifting the annotations in $r_3, \dots, r_5$ to the associated rules. Also, associate the confidence level $\langle [1, 1], [0, 0] \rangle$ with r_1, r_2 . For uniformity and ease of comparison, assume the doubt ranges are all $[0, 0]$. As an example, let the conjunctive mode used in r_1, r_2 be independence and let the disjunctive mode used be positive correlation (or, in this case, even ignorance!). Then $lfp(T_P)$ would assign the confidence $\langle [1, 1], [0, 0] \rangle$ to $p(1, 2)$, which agrees with our intuition. Our point, however, is **not** that intersection is a “wrong” mode. Rather, we stress that different combination rules (modes) are appropriate for different situations. ■

Example 7.2

Now consider the following pf-program (r_1 and r_2 are the same as previous example):

- $r_1: p(X, Y) : [V_1 \times V_3, V_2 \times V_4] \leftarrow e(X, Z) : [V_1, V_2], \quad p(Z, Y) : [V_3, V_4].$
- $r_2: p(X, Y) : [V_1, V_2] \leftarrow e(X, Y) : [V_1, V_2].$
- $r_6: e(1, 2) : [0, 1].$
- $r_7: e(1, 1) : [0, 0.9].$

¹² To be precise, each *basic formula*, which is a conjunction or a disjunction of atoms, is annotated.

In this case, the least fixpoint of T_P^{NS} is only attained at ω and it assigns the range $[0, 0]$ to $p(1, 1)$ and $p(1, 2)$. Again, the result is unintuitive for this example. Since T_P^{NS} is not continuous, one can easily write programs such that no reasonable approximation to $lfp(T_P^{NS})$ can be obtained by iterating T_P^{NS} an arbitrary (finite) number of times. (E.g., consider the program obtained by adding the rule r_8 : $q(X, Y) : [1, 1] \leftarrow p(X, Y) : [0, 0]$ to $\{r_1, r_2, r_6, r_7\}$.) Notice that as long as one uses any arithmetic annotation function such that the probability of the head is less than the probability of the subgoals of r_1 (which is a reasonable annotation function), this problem will arise. The problem (for the unintuitive behavior) lies with the mode for disjunction. Again, we emphasize that different combination rules (modes) are appropriate for different situations.

Now, consider the p-program corresponding to the annotated program $\{r_1, r_2, r_6, r_7\}$, obtained in the same way as was done in Example 7.1. Let the conjunctive mode used in r_1, r_2 be independence and let the disjunctive mode be positive correlation or ignorance. Then $lfp(T_P)$ would assign the confidence level $\langle [0, 1], [0, 0] \rangle$ to $p(1, 2)$. This again agrees with our intuition. As a last example, suppose we start with the confidence $\langle [0, 0.1], [0, 0] \rangle$ for $e(1, 2)$ instead. Then under positive correlation (for disjunction) $lfp(T_P)(p(1, 2)) = \langle [0, 0.1], [0, 0] \rangle$, while ignorance leads to $lfp(T_P)(p(1, 2)) = \langle [0, 1], [0, 0] \rangle$. The former makes more intuitive sense, although the latter (more conservative under $\leq_p$) is obviously not wrong. Also, in the latter case, the lfp is reached only at ω . ■

Now, we discuss termination and complexity issues of p-programs. Let the *closure ordinal* of T_P be the smallest ordinal α such that $T_P \uparrow \alpha = lfp(T_P)$. We have the following

Fact 7.1

Let P be any p-program. Then the closure ordinal of T_P can be as high as ω but no more.

Proof. The last p-program discussed in Example 7.2 has a closure ordinal of ω . Since T_P is continuous (Theorem 5.1) its closure ordinal is at most ω . ■

Definition 7.1

(*Data Complexity*) We define the *data complexity* (Vardi, M.Y., 1985) of a p-program P as the time complexity of computing the least fixpoint of T_P as a function of the size of the database, i.e. the number of constants occurring in P ¹³.

It is well known that the data complexity for datalog programs is polynomial. An important question concerning any extension of DDBs to handle uncertainty is whether the data complexity is increased compared to datalog. We can show that under suitable restrictions (see below) the data complexity of p-programs is polynomial time. However, the proof cannot be obtained by (straightforward extensions of) the classical argument for the data complexity for datalog. In the classical case,

¹³ With many rule-based systems with uncertainty, we cannot always separate EDB and IDB predicates, which explains this slightly modified definition of data complexity.

once a ground atom is derived during bottom-up evaluation, future derivations of it can be ignored. In programming with uncertainty, complications arise because we *cannot* ignore alternate derivations of the same atom: the confidences obtained from them need to be combined, reinforcing the overall confidence of the atom. This calls for a new proof technique. Our technique makes use of the following additional notions.

Define a *disjunctive derivation tree* (DDT) to be a well-formed DPT (see Section 6 for a definition) such that every goal and every substitution labeling any node in the tree is ground. Note that the height of a DDT with no failure nodes is an odd number (see Remark 7 at the beginning of Section 6). We have the following results.

Proposition 7.1

Let P be a p-program and A any ground atom in B_P . Suppose the confidence determined for A in iteration $k \geq 1$ of bottom-up evaluation is c . Then there exists a DDT T of height $2k - 1$ for A such that the confidence associated with A by T is exactly c .

Proof. The proof is by induction on k .

Basis: $k = 1$. In iteration 1, bottom-up evaluation essentially collects together all edb facts (involving ground atoms) and determines their confidences from the program. Without loss of generality, we may suppose there is at most one edb fact in P corresponding to each ground atom (involving an edb predicate). Let A be any ground atom whose confidence is determined to be c in iteration 1. Then there is an edb fact $r : A \xleftarrow{c}$ in P . The associated DDT for A corresponding to this iteration is the tree with root labeled A and a rule child labeled r . Clearly, the confidence associated with the root of this tree is c , and the height of this tree is 1 ($= 2k - 1$, for $k = 1$).

Induction: Assume the result for all ground atoms whose confidences are determined (possibly revised) in iteration k . Suppose A is a ground atom whose confidence is determined to be c in iteration $k + 1$. This implies there exist ground instances of rules $r_1 : A \xleftarrow{c_{r_1}} B_1, \dots, B_m; \mu_1, \mu_A, \dots; r_k : A \xleftarrow{c_{r_k}} C_1, \dots, C_n; \mu_k, \mu_A$ such that (i) the confidence of $B_i, \dots, C_j$ computed at the end of iteration k is $c_i, \dots, d_j$, and (ii) $c = (c_{r_1} \wedge_{\mu_1} (\bigwedge_{\mu_1} \{c_1, \dots, c_m\}) \vee_{\mu_A} \dots \vee_{\mu_A} (c_{r_k} \wedge_{\mu_k} (\bigwedge_{\mu_k} \{d_1, \dots, d_n\}))$, where $\vee_{\mu_A}$ is the disjunctive mode for the predicate A . By induction hypothesis, there are DDTs $T_{B_1}, \dots, T_{B_m}, \dots, T_{C_1}, \dots, T_{C_n}$, each of height $2k - 1$ or less, for the atoms $B_1, \dots, B_m, \dots, C_1, \dots, C_n$ which exactly compute the confidences $c_1, \dots, c_m, \dots, d_1, \dots, d_n$ respectively, corresponding to iteration k . Consider the tree T_{k+1} for A by (i) making $r_1, \dots, r_k$ rule children of the root and (ii) making the $T_{B_1}, \dots, T_{B_m}, (\dots, T_{C_1}, \dots, T_{C_n})$ subtrees of $r_1, (\dots, r_k)$. It is trivial to see that T_{k+1} is a DDT for A and its height is $2 + 2k - 1 = 2(k + 1) - 1$. Further the confidence T_{k+1} computes for the root A is exactly $(c_{r_1} \wedge_{\mu_1} (\bigwedge_{\mu_1} \{c_1, \dots, c_m\}) \vee_{\mu_A} \dots \vee_{\mu_A} (c_{r_k} \wedge_{\mu_k} (\bigwedge_{\mu_k} \{d_1, \dots, d_n\}))$. This completes the induction and the proof. ■

Proposition 7.1 shows each iteration of bottom-up evaluation corresponds in an essential manner to the construction of a set of DDTs one for each distinct ground

atom whose confidence is determined (or revised) in that iteration. Our next objective is to establish a termination bound on bottom-up evaluation.

Definition 7.2 (Branches in DDTs)

DDT branches are defined similar to those of DPT. Let T be a DDT. Then a branch of T is a subtree of T , defined as follows.

- (i) The root belongs to every branch.
- (ii) whenever a goal node belongs to a branch, exactly one of its rule children, belongs to the branch.
- (iii) whenever a rule node belongs to a branch, all its goal children belong to the branch.

Definition 7.3 (Simple DDTs)

Let A be a ground atom and T any DDT (not necessarily for A). Then T is *A-non-simple* provided it has a branch containing two goal nodes u and v such that u is an ancestor of v and both are labeled by atom A . A DDT is *A-simple* if it is not *A-non-simple*. Finally, a DDT is *simple* if it is *A-simple* for every atom A .

Let T be a DDT and B_i be a branch of T in which an atom A appears. Then we define the *number of violations of simplicity* of B_i with respect to A to be one less than the total number of times the atom A occurs in B_i . The number of violations of the simplicity of the DDT T with respect to A is the sum of the number of violations of the branches of T in which A occurs. Clearly, T is *A-simple* exactly when the number of violations with respect to A is 0. Our first major result of this section follows.

Theorem 7.1

Let P be a p-program such that only positive correlation is used as the disjunctive mode for recursive predicates. Let $\max\{\text{height}(T_A) \mid A \in B_P, \text{ and } T_A \text{ is any simple DDT for } A\} = 2k - 1, k \geq 1$. Then at most $k + 1$ iterations of naive bottom-up evaluation are needed to compute the least fixpoint of T_P .

Essentially, for p-programs P satisfying the conditions mentioned above, the theorem (i) shows that naive bottom-up evaluation of P is guaranteed to terminate, and (ii) establishes an upper bound on the number of iterations of bottom-up evaluation for computing the least fixpoint, in terms of the maximum height of any simple tree for any ground atom. This is the first step in showing that p-programs of this type have a polynomial time data complexity. We will use the next three lemmas (Lemmas 7.1–7.3) in proving this theorem.

Lemma 7.1

Let $A \in B_P$ be any ground atom, and let T be a DDT for A corresponding to $T_P \uparrow l$, for some l . Suppose T is *B-non-simple*, for some atom B . Then there is a DDT T' for A with the following properties:

- (i) the certainty of A computed by T' equals that computed by T .
- (ii) the number of violations of simplicity of T' with respect to B is less than that of T .

Proof. Let T be the DDT described in the hypothesis of the claim. Let A be the label of the root u of T , and assume without loss of generality that B is identical to A . (The case when B is distinct from A is similar.) Let v be the last goal node from the root down (e.g. in the level-order), which is distinct from the root and is labeled by A . Since T corresponds to applications of the T_P operator, we have the following.

(*) Every branch of v must be isomorphic to some branch of u which does not contain the node v .

This can be seen as follows. Let $p < l$ be the iteration such that the subtree of T rooted at v , say T_v , corresponds to $T_P \uparrow p$. Then clearly, every rule applicable in iteration p is also applicable in iteration k . This means every branch of T_v constructed from a sequence of rule applications is also constructible in iteration k and hence there must be a branch of T that is isomorphic to such a branch. It follows from the isomorphism that the isomorphic branch of T cannot contain the node v .

Associate a logical formula with each node of T as follows.

- (i) The formula associated with each (rule) leaf is **true**.
- (ii) The formula associated with a goal node with rule children $r_1, \dots, r_m$ and associated formulas $F_1, \dots, F_m$, is $F_1 \vee \dots \vee F_m$.
- (iii) The formula associated with a rule parent with goal children $g_1, \dots, g_q$ and associated formulas $G_1, \dots, G_q$ is $G_1 \wedge \dots \wedge G_q$.

Let the formula associated with the node v be F . To simplify the exposition, but at no loss of generality, let us assume that in T , every goal node has exactly two rule children. Then the formula associated with the root u can be expressed as $E_1 \vee (E_2 \wedge (E_3 \vee (\dots E_{s-1} \wedge (E_s \vee F)) \dots))$.

By (*) above, we can see that F logically implies E_1 , $F \Rightarrow E_1$. By the structure of a DDT, we can then express E_1 as $(F \vee G)$, for some formula G . Construct a DDT T' from T by deleting the parent of the node v , as well as the subtree rooted at v . We claim that

(**) The formula associated with the root of T' is equivalent to that associated with the root of T .

To see this, notice that the formula associated with the root of T can now be expressed as $(F \vee G) \vee (E_2 \wedge (E_3 \vee (\dots E_{s-1} \wedge (E_s \vee F)) \dots))$. By simple application of propositional identities, it can be seen that this formula is equivalent to $(F \vee G) \vee (E_2 \wedge (E_3 \vee (\dots E_{s-1} \wedge (E_s)) \dots))$. But this is exactly the formula associated with the root of T' , which proves (**).

Finally, we shall show that $\vee_{pc}$, together with any conjunctive mode, satisfy the following absorption laws:

$$\begin{aligned} a \vee_{pc} (a \wedge_{\mu} b) &= a. \\ a \wedge_{pc} (a \vee_{\mu} b) &= a. \end{aligned}$$

The first of these laws follows from the fact that for all modes μ we consider in this paper, $(a \wedge_{\mu} b) \leq_t a$, where $\leq_t$ is the lattice ordering. The second is the dual of the first.

In view of the absorption laws, it can be seen that the certainty for A computed by T' above is identical to that computed by T . This proves the lemma, since T' has at least one fewer violations of simplicity with respect to A . ■

Lemma 7.2

Let T be a DDT for an atom A . Then there is a simple DDT for A such that the certainty of A computed by it is identical to that computed by T .

Proof. Follows by an inductive argument using Lemma 7.1. ■

Lemma 7.3

Let A be an atom and $2h - 1$ be the maximum height of any simple DDT for A . Then certainty of A in $T_P \uparrow l$ is identical to that in $T_P \uparrow h$, for all $l \geq h$.

Proof. Let T be the DDT for A corresponding to $T_P \uparrow l$. Note that $\text{height}(T) = 2l - 1$. Let c represent the certainty computed by T for A , which is $c = T_P \uparrow l(A)$. By Lemma 7.2, there is a simple DDT, say T' , for A , which computes the same certainty for A as T . Clearly, $\text{height}(T') \leq 2h - 1$. Let c' represent the certainty computed by T' for A , $c = c'$. By the soundness theorem, and monotonicity of T_P , we can write $c' \leq T_P \uparrow h(A) \leq T_P \uparrow l(A) = c$. It follows that $T_P \uparrow l(A) = T_P \uparrow h(A)$. ■

Now we can complete the proof of Theorem 7.1.

Proof of Theorem 7.1. Let $2k - 1$ be the maximum height of any simple DDT for any atom. It follows from the above Lemmas that the certainty of any atom in $T_P \uparrow l$ is identical to that in $T_P \uparrow k$, for all $l \geq k$, from which the theorem follows. ■

It can be shown that the height of simple DDTs is polynomially bounded by the database size. This makes the above result significant. This allows us to prove the following theorem regarding the data complexity of the above class of p-programs.

Theorem 7.2

Let P be a p-program such that only positive correlation is used as the disjunctive mode for recursive predicates. Then its least fixpoint can be computed in time polynomial in the database size. In particular, bottom-up naive evaluation terminates in time polynomial in the size of the database, yielding the least fixpoint.

Proof. By Theorem 7.1 we know that the least fixpoint model of P can be computed in at most $k + 1$ iterations where $h = 2k - 1$ is the maximum height of any simple DDT for any ground atom with respect to P (k iterations to arrive at the fixpoint, and one extra iteration to verify that a fixpoint has been reached.) Notice that each goal node in a DDT corresponds to a database predicate. Let K be the maximum arity of any predicate in P , and n be the number of constants occurring in the program. Notice that under the data complexity measure (Definition 7.1) K is a constant. The maximum number of distinct goal nodes that can occur in any branch of a simple DDT is n^K . This implies the height h above is clearly a polynomial in the database size n . We have thus shown that bottom-up evaluation of the least fixpoint terminates in a polynomial number of iterations. The fact that the amount of work done in each iteration is polynomial in n is easy to see. The theorem follows. ■

We remark that our proof of Theorem 7.2 implies a similar result for van Emden’s framework. To our knowledge, this is the first polynomial time result for rule-based programming with (probabilistic) uncertainty¹⁴. We should point out that the polynomial time complexity is preserved whenever modes other than positive correlation are associated with non-recursive predicates (for disjunction). More generally, suppose R is the set of all recursive predicates and N is the set of non-recursive predicates in the KB, which are possibly defined in terms of those in R . Then any modes can be freely used with the predicates in N while keeping the data complexity polynomial. Finally, if we know that the data does not contain cycles, we can use any mode even with a recursive predicate and still have a polynomial time data complexity. We also note that the framework of annotation functions used in (Kifer & Subrahmanian, 1992) enables an infinite family of modes to be used in propagating confidences from rule bodies to heads. The major differences with our work are (i) in (Kifer & Subrahmanian, 1992) a fixed “mode” for disjunction is imposed unlike our framework, and (ii) they do not study the complexity of query answering, whereas we establish the conditions under which the important advantage of polynomial time data complexity of classical datalog can be retained. More importantly, our work has generated useful insights into how modes (for disjunction) affect the data complexity. Finally, a note about the use of positive correlation as the disjunctive mode for recursive predicates (when data might contain cycles). The rationale is that different derivations of such recursive atoms could involve some amount of overlap (the degree of overlap depends on the data). Now, positive correlation (for disjunction) tries to be conservative (and hence sound) by assuming the extent of overlap is maximal, so the combined confidence of the different derivations is the least possible (under $\leq_t$). Thus, it *does* make sense even from a practical point of view.

8 Conclusions

We motivated the need for modeling both belief and doubt in a framework for manipulating uncertain facts and rules. We have developed a framework for probabilistic deductive databases, capable of manipulating both belief and doubt, expressed as probability intervals. Belief doubt pairs, called confidence levels, give rise to a rich algebraic structure called a trilattice. We developed a probabilistic calculus permitting different modes for combining confidence levels of events. We then developed the framework of p-programs for realizing probabilistic deductive databases. p-Programs inherit the ability to “parameterize” the modes used for combining confidence levels, from our probabilistic calculus. We have developed a declarative semantics, a fixpoint semantics, and proved their equivalence. We have also provided a sound and complete proof procedure for p-programs. We have shown that under disciplined use of modes, we can retain the important advantage

¹⁴ It is straightforward to show that the data complexity for the framework of (Ng & Subrahmanian, 1992) is polynomial, although the paper does not address this issue. However, that framework only allows constant annotations and is of limited expressive power.

of polynomial time data complexity of classical datalog, in this extended framework. We have also compared our framework with related work with respect to the aspects of termination and intuitive behavior (of the semantics). The parametric nature of modes in p-programs is shown to be a significant advantage with respect to these aspects. Also, the analysis of trilattices shows insightful relationships between previous work (*e.g.* Ng and Subrahmanian (Ng & Subrahmanian, 1992; Ng & Subrahmanian, 1993)) and ours. Interesting open issues which merit further research include (1) semantics of p-programs under various trilattice orders and various modes, including new ones, (2) query optimization, (3) handling inconsistency in a framework handling uncertainty, such as the one studied here.

Acknowledgments

The authors would like to thank the anonymous referees for their careful reading and their comments, many of which have resulted in significant improvements to the paper.

References

- Abiteboul, S., Kanellakis, P., & Grahne, G. (1991). On the representation and querying of sets of possible worlds. *Theoretical computer science*, **78**, 159–187.
- Baldwin, J. F. (1987). Evidential support logic programming. *Journal of fuzzy sets and systems*, **24**, 1–26.
- Baldwin, J. F., & Monk, M. R. M. (1987). *Evidence theory, fuzzy logic, and logic programming*. Tech. Report ITRC No. 109. University of Bristol, Bristol, UK.
- Barbara, D., Garcia-Molina, H., & Porter, D. (1990). A probabilistic relational data model. *Pages 60–64 of: Proc. advancing database technology, EDBT, 90*.
- Barbara, D., Garcia-Molina, H., & Porter, D. (1992). The management of probabilistic data. *IEEE transactions on knowledge and data engineering*, **4**(5), 487–502.
- Blair, H. A., & Subrahmanian, V. S. (1989a). Paraconsistent foundations for logic programming. *Journal of non-classical logic*, **5**(2), 45–73.
- Blair, H. A., & Subrahmanian, V. S. (1989b). Paraconsistent logic programming. *Theoretical computer science*, **68**, 135–154.
- Boole, G. (1854). *The laws of thought*. London: Mcmillan.
- Carnap, R. (1962). *The logical foundations of probability*. University of Chicago Press. 2nd. Edn.
- Debray, S., & Ramakrishnan, R. (1994). *Generalized Horn clause programs*. manuscript.
- Dekhtyar, A., & Subrahmanian, V. S. (1997). Hybrid probabilistic program. *Pages 391–405 of: Proc. 14th intl. conf. on logic programming*.
- Dong, F., & Lakshmanan, L.V.S. (1992). Deductive databases with incomplete information. *Pages 303–317 of: Joint intl. conf. and symp. on logic programming*. (extended version available as Tech. Report, Concordia University, Montreal, 1993).
- Fagin, R., Halpern, J., & Megiddo, N. (1990). A logic for reasoning about probabilities. *Information and computation*, **87**(1/2), 78–128.
- Fenstad, J. E. (1980). The structure of probabilities defined on first-order languages. *Pages 251–262 of: Jeffrey, R. C. (ed), Studies in inductive logic and probabilities, volume 2*. University of California Press.

- Fitting, M. C. (1988). Logic programming on a topological bilattice. *Fundamenta informaticae*, **11**, 209–218.
- Fitting, M. C. (1991). Bilattices and the semantics of logic programming. *Journal of logic programming*, **11**, 91–116.
- Fitting, M. C. 1995 (February). Private Communication.
- Frechet, M. (1935). Generalizations du theoreme des probabilités totales. *Fund. math.*, **25**, 379–387.
- Gaifman, H. (1964). Concerning measures in first order calculi. *Israel j. of math.*, **2**, 1–17.
- Ginsburg, M. (1988). Multivalued logics: A uniform approach to reasoning in artificial intelligence. *Computational intelligence*, **4**, 265–316.
- Güntzer, U., Kießling, W., & Thöne, H. (1991). New directions for uncertainty reasoning in deductive databases. *Pages 178–187 of: Proc. ACM SIGMOD intl. conf. on management of data*.
- Hailperin, T. (1984). Probability logic. *Notre dame j. of formal logic*, **25**(3), 198–212.
- Halpern, J. Y. (1990). An analysis of first-order logics of probability. *Journal of AI*, **46**, 311–350.
- Kifer, M., & Li, A. (1988). On the semantics of rule-based expert systems with uncertainty. *Pages 102–117 of: Gyssens, M., Paradaens, J., & van Gucht, D. (eds), 2nd intl. conf. on database theory*. Bruges, Belgium: Springer-Verlag LNCS-326.
- Kifer, M., & Lozinskii, E. L. (1989). A logic for reasoning with inconsistency. *Pages 253–262 of: Proc. 4th IEEE symp. on logic in computer science (LICS)*. Asilomar, CA: IEEE Computer Press.
- Kifer, M., & Lozinskii, E. L. (1992). A logic for reasoning with inconsistency. *Journal of automated reasoning*, **9**(2), 179–215.
- Kifer, M., & Subrahmanian, V. S. (1992). Theory of generalized annotated logic programming and its applications. *Journal of logic programming*, **12**, 335–367.
- Lakshmanan, L. V. S. (1994). An epistemic foundation for logic programming with uncertainty. *Proc. intl. conf. on foundations of software technology and theoretical computer science*. Madras, India: Springer Verlag. Lecture Notes in Computer Science, vol. 880.
- Lakshmanan, L. V. S., & Sadri, F. (1994a). Modeling uncertainty in deductive databases. *Pages 724–733 of: Proc. intl. conf. on database and expert systems applications (DEXA '94)*. Athens, Greece: Springer-Verlag, LNCS-856.
- Lakshmanan, L. V. S., & Sadri, F. (1994b). Probabilistic deductive databases. *Pages 254–268 of: Proc. intl. logic programming symposium*. Ithaca, NY: MIT Press.
- Lakshmanan, L. V. S., & Sadri, F. (1997). Uncertain deductive databases: A hybrid approach. *Information Systems*, **22**(8), 483–508.
- Lakshmanan, L. V. S., & Shiri, N. (1997). A parametric approach to deductive databases with uncertainty. *Accepted to the IEEE transactions on knowledge and data engineering*. (A preliminary version appeared in Proc. Intl. Workshop on Logic in Databases (LID'96), Springer-Verlag, LNCS-1154, San Miniato, Italy).
- Lakshmanan, L. V. S., N. Leone, R. Ross, & V. S. Subrahmanian. (1997). ProbView: A Flexible Probabilistic Database System. *ACM Transactions on Database Systems*, **22**(3), 419–469.
- Liu, Y. (1990). Null values in definite programs. *Pages 273–288 of: Proc. north american conf. on logic programming*.
- Ng, R. T. (1997). Semantic, consistency, and query processing of empirical deductive databases. *IEEE Transactions on Knowledge and Data Engineering*, **9**(1), 32–495.
- Ng, R. T., & Subrahmanian, V. S. (1991). *Relating Dempster-Shafer theory to stable semantics*. Tech. Report UMIACS-TR-91-49, CS-TR-2647. Institute for Advanced Com-

- puter Studies and Department of Computer Science University of Maryland, College Park, MD 20742.
- Ng, R. T., & Subrahmanian, V. S. (1992). Probabilistic logic programming. *Information and computation*, **101**(2), 150–201.
- Ng, R. T., & Subrahmanian, V. S. (1993). A semantical framework for supporting subjective and conditional probabilities in deductive databases. *Automated reasoning*, **10**(2), 191–235.
- Ng, R. T., & Subrahmanian, V. S. (1994). Stable semantics for probabilistic deductive databases. *Information and computation*, **110**(1), 42–83.
- Nilsson, N. (1986). Probabilistic logic. *AI journal*, **28**, 71–87.
- Sadri, F. (1991a). Modeling uncertainty in databases. *Pages 122–131 of: Proc. 7th IEEE intl. conf. on data engineering*.
- Sadri, F. (1991b). Reliability of answers to queries in relational databases. *IEEE transactions on knowledge and data engineering*, **3**(2), 245–251.
- Schmidt, H., Steger, N., Guntzer, U., Kießling, W., Azone, A., & Bayer, R. (1989). Combining deduction by certainty with the power of magic. *Pages 103–122 of: Proc. 1st intl. conf. on deductive and object-oriented databases*.
- Steger, N., Schmidt, H., Guntzer, U., & Kießling, W. (1989). Semantics and efficient compilation for quantitative deductive databases. *Pages 660–669 of: Proc. IEEE intl. conf. on data engineering*.
- Subrahmanian, V. S. (1987). On the semantics of quantitative logic programs. *Pages 173–182 of: Proc. 4th IEEE symposium on logic programming*.
- Ullman, J. D. (1989). *Principles of database and knowledge-base systems*. Vol. II. Maryland: Computer Science Press.
- van Emden, M. H. (1986). Quantitative deduction and its fixpoint theory. *Journal of logic programming*, **4**(1), 37–53.
- Vardi, M.Y. (1985). Querying logical databases. *Pages 57–65 of: Proc. 4th ACM SIGACT-SIGMOD symposium on principles of database systems*.